Results from CMS Test Beam and Run2

Sunanda Banerjee, Fermilab Vladimir Ivantchenko, Tomsk State University, Russia & CERN Geant4 Collaboration Meeting August 28, 2018

Introduction



- CMS experiment uses Geant4 toolkit as the simulation engine
- Adaptation of a new Geant4 version or a new Physics List requires validation of the model predictions with some of the existing data
- The current validation results are intended for the version of Geant4.10.4 (December 2017), which is adopted for the 2018 production
 - Results are compared with the 2017 version of CMS simulation which are based on Geant4.10.2.p02
- Additionally to the new Geant4 version, other modifications were done to CMS simulation. The most significant one is the use of the new VecGeom library, which is also tested in this analysis.
- There are two sources of data used for validation:
 - 2006 test beam runs in the SPS H2 beam line with prototypes of barrel hadron calorimeter (HB) module and one supermodule of barrel electromagnetic calorimeter
 - Results published in EPJ C60 (2009) 359 and used in tuning earlier CMS simulation
 - Low luminosity runs with the CMS detector taken during 2016B run period using Zero Bias and Minimum Bias triggers

Geant4 Physics List and Monte Carlo Sample

- **G4**
- From 2017 onward simulation of CMS detector is done using Geant4.10.2.p02 and with FTFP_BERT_EMM Physics List
- The main part of this Physics List is FTFP_BERT:
 - recommended by the Geant4 collaboration as default physics configuration
 - the hadronic part of FTFP_BERT_EMM is identical to that of FTFP_BERT
- EMM provides a special configuration of Geant4 electromagnetic physics which includes
 - applied production cuts for gamma processes
 - simplified step limitation by multiple scattering of e⁺/e⁻
 - default step limitation by multiple scattering of e[±] inside sampling calorimeters
- This Physics List provides good CPU performance as well as adequate accuracy for calorimeter response simulation
- For Monte Carlo events are generated using Geant4 versions 10.2.p02 and 10.4:
 - 50k events at each beam energy for the said type and for calibration generate 50k electron events in setups with and without EB
 - 100k single particle event sample using a flat energy distribution between 1 and 20 GeV with a given admixture of pions, kaons and protons and anti-protons (as expected in minimum bias sample)

2006 TestBeam Data

- The data correspond to single particle response due to well identified particles over a large momentum range (2 to 350 GeV)
- The results consist of the energy distributions for well identified particles at a fixed momentum
 - Particle identification is rather good for beam momenta at or below 9 GeV
- Use the setup described within CMSSW to simulate events with single particles.
- Both the calorimeters are calibrated using 50 GeV electron beam





:henko

Test Beam Analysis



- Events are simulated only till the simulation hit level (including saturation effect as in Birk's law)
- Effect of electronics and detector noise is taken care of by adding Gaussian noise separately for ECAL and HCAL
 - RMS_{ECAL} = 0.362 GeV
 - RMS_{HCAL} = 0.640 GeV
- The detector components in the beam line are described in the simulation package and the cuts which are used for data analysis are also used for analyzing the Monte Carlo Sample
- Exclude hits in the outer hadron calorimeter and use a time cut of 100 ns
- Energy in the calorimeter is summed up around the beam spot
 - 7x7 matrix of crystals for ECAL
 - 3x3 towers for HCAL
- 50 GeV electrons are used for defining energy scales of ECAL as well as HCAL. Energy is measured as
 - Evis = $E_{ECAL} * f_{ECAL} + E_{HCAL} * f_{HCAL}$
 - f_{ECAL} = 1.01, f_{HCAL} ~105 (for FTFP_BERT_EMM Physics List)

Mean response to pion beams





Mean response to proton & anti-proton beams



Energy resolution for π and proton





Geant4 Collaboration Meeting

8

Isolated Charged Hadrons

- Compare ratio of calorimeter energy measurement to track momentum for isolated charged hadrons between data and MC
- Follow the same analysis strategy as in the PAS JME-10-008 applying to the Run-2 data
 - Select good charged tracks reaching the calorimeter surface
 - Impose isolation of these charged particles
 - propagate all tracks in the event to the calorimeter surface and study momentum of tracks (selected with a loose goodness criteria) reaching ECAL (HCAL) within a matrix of 31x31 (7x7) around the impact point of the selected track
 - study energy deposited in an annular region in ECAL (HCAL) between 15x15 and 11x11 (7x7 and 5x5) matrices for isolation against neutral particles

• Final cuts

- No addition; tracks in the isolation region
- Energy cut of 2 GeV for neutral isolation
- No additional good primary vertex in the event (to reduce PileUp effect)

- Look at tracks in 4 different regions: two in the barrel, one in the endcap and one in the transition region
- Measure energy by combining energy measurements from a matrix of NxN cells around the cell hit by the extrapolated track to the calorimeter surface. Two versions of NxN matrix used:
 - 7x7 matrix for ECAL and 3x3 matrix for HCAL (better purity)
 - 11x11 matrix for ECAL and 5x5 matrix for HCAL (better containment)
- For the data use two low luminosity data sets from the 2016B run period
 - Distributions from Zero Bias and Minimum Bias triggers agree quite well
 - Combine these two data sets and compare that with Monte Carlo

Geant4 Collaboration Meeting

S. Banerjee/V. Ivantchenko

Combined Calorimeter Energy (7x7+3x3 matrix)

Combined Calorimeter Energy (11x11+5x5 matrix)

Collision Data (FTFP)

• The level of disagreement between data and MC is between 1.5% to 5.7% for the Geant4 version 10.4 depending on the region of the detector

Mean level of disagreement between MC and data

	(E _{7x7} +H _{3x3})/p 10.2.p02	(E _{7x7} +H _{3x3})/p 10.4	(E _{11x11} +H _{5x5})/p 10.2.p02	(E _{11x11} +H _{5x5})/p 10.4
Barrel 1	(2.4±0.4)%	(5.7±0.4)%	(2.6±0.4)%	(4.0±0.4)%
Barrel 2	(3.6±0.4)%	(4.0±0.4)%	(2.2±0.4)%	(2.6±0.4)%
Transition	(4.9±0.5)%	(4.8±0.5)%	(2.2±0.5)%	(2.9±0.5)%
Endcap	(3.1±0.3)%	(3.0±0.5)%	(1.5±0.5)%	(1.5±0.5)%

Summary

- Predictions from the Physics List FTFP_BERT_EMM from Geant4 versions 10.2.p02 and 10.4 are compared with the collision data from CMS as well as with energy distributions from 2006 test beam data
- The level of agreement between data and Monte Carlo is reasonable for both the versions of Geant4 for collision data and similar to earlier comparisons for test beam data
 - pion data show slightly wider energy distributions than MC predictions
 - antiproton response is about 5% over predicted
 - kaon response is about 10% under predicted

Additional Slides

CMS Detector

Selection of Isolated Tracks

- Select good charged tracks
 - p_T > 1 GeV
 - Chi-square/d.o.f. < 5
 - # of layers crossed > 8
 - Fractional error on p < 0.1
 - No missed hits in inner/outer layers
 - originates close to primary vertex (< 0.2 mm in x-y and r-z planes)
 - reach the HCAL surface
- Impose isolation of these charged particles
 - propagate track to calorimeter surface and study momentum of tracks (selected with looser criteria) reaching ECAL (HCAL) within a matrix of 31x31 (7x7) around the impact point of the selected track
 - study energy deposited in an annular region in ECAL (HCAL) between 15x15 and 11x11 (7x7 and 5x5) matrices for neutral isolation
- Final cuts
 - No tracks in the isolation region
 - Energy cut of 2 GeV for neutral isolation