

OPERATION OF A 10kW@1.3GHz SOLID STATE AMPLIFIER AT THE S.C. LINAC ELBE

HARTMUT BÜTTIG FOR

P.DUPIRE, O.GONELLA, L.MARTINACHE, M.WEISS
J.ILIEV, (BRUKER BioSpin Wissembourg / France)

P.MICHEL, R.SCHURIG, G.STAATS (FZD-Dresden)



Forschungszentrum
Dresden Rossendorf


MOTIVATION

- ELBE UPGRADE AFTER 10 YEARS OF OPERATION (MANY ACTIVITIES)
 - ONE TOPIC IS: DOUBLING THE RF POWER
-
- Has an impact on:
 - RF power amplifiers, RF - couplers, WG-windows; diagnostics, beam dumps, water cooling, mains power...



Forschungszentrum
Dresden Rossendorf

Just to remember:



SC-LINAC: 40 MeV, 1mA (CW), based on 4 Tesla Cavities



Forschungszentrum
Dresden Rossendorf

Thermionic

DC Gun

250 kV


≤ 260 MHz

77

pC(1mA*13MHz)

~ 500 ps

~ 10 mm mrad




RF Bunchers

260 MHz

+1,3GHz

compr. $\sim 100:1$




Linac

1,3 GHz

~ 20 MeV@10 MeV/m

< 1 mA CW





Linac

1,3 GHz

~ 20 MeV@10MV/m

< 1 mA CW



SRF photo gun

9.5 MeV

≤ 13 MHz

80pC / 1nC / 2.5 nC

$\sim 5-20$ ps

$\sim 1.5-3$ mm mrad



4 x 10kW CW

Klystrons: CPI

VKL7811St

(-1dB comp.: 8.5 kW)



Forschungszentrum
Dresden Rossendorf

ELBE-UPGRADE: RF RELATED ACTIVITIES

- **RESONANT RING** (since 2005):
 - Conditioning of RF couplers, WG-windows,
 - (NIM A 612 (2010) 427 - 437)
- **DOUBLING THE RF - POWER:**
 - Test of a 16 kW IOT at a SC-Cavity (2008),
(Good cooperation with Bruker BioSpin+CPI)
 - (SRF 2009, TUPP026)



Forschungszentrum
Dresden Rossendorf

Remarks on 16kW - IOT

- Test in 2008 with beam in principle ok
- Compared with a 10kW VKL7811St Klystron (permanent magnet system) IOT is more exp.
- Solid state technology becomes more and more competitive.
- (costs: 12...16 €/W@1.3GHz)
- The „border line between tube- and SSA-technology“ may be in the range of 20 kW at present, but moving up quickly



Forschungszentrum
Dresden Rossendorf

SOLID STATE AMPLIFIER (SSA)

- ELBE was focused on IOT but not happy.
- **INSPIRATION TO SSA-Technology by:**
 - BRUKER EXP. (NMR/MRI-SSA Technology)
 - BRUKER EXP. (Big SSA for Orsay)
 - BRUKER 1kW@1.3GHz CW IOT-drivers
 - CWRF 2008 GENEVA (The trend was clear !)



Forschungszentrum
Dresden Rossendorf

Start 1/2009; Prototype 1/2010

- Email: **6.Jan 2009**: (H.Büttig to L.Martinache)
- End of 2008 we discussed briefly the possibility to test a SSA 1.3GHz at ELBE...hw?
- Answer: We are currently working on a water cooled 800W - 1000W SSA. We will do the first tests in a few weeks. Next step is....
6 modules ... in May 2009. 10kW at SRF Berlin
- Delivery of the complete 10kW SSA: **Jan2010**



Forschungszentrum
Dresden Rossendorf

10kW transmitter presented at SRF Berlin October 2009




- 42U cabinet
- WR650 waveguide output at the top
- water cooled power modules
- water cooled driver
- built in 24kW 28V power supply



Forschungszentrum
Dresden Rossendorf

BLOCK DIAGRAM




8 RF-power units in parallel

24kW 28V power supply




current distribution
via copper bars



Forschungszentrum
Dresden Rossendorf

RF power



-1dB compression point at 8.5kW CW
-2dB compression point 9.1kW CW
-2.5dB compression point 9.5kW CW


-10kW achieved in pulsed mode

typical flow rates for CW 35l/min



Forschungszentrum
Dresden Rossendorf


Bandwidth at 8 kW



Forschungszentrum
Dresden Rossendorf



LINEARITY

Gain and phase variations over dynamic range



Forschungszentrum
Dresden Rossendorf

RAISE TIME and FALL TIME




measured at 8kW output power
rise time $\approx 20\text{ns}$ fall time $\approx 60\text{ns}$



Forschungszentrum
Dresden Rossendorf

SPURIOUS SIGNALS (200kHz)




Pout=8 kW
Source: SMR20
R&S:FSQ26 (Aly.)
Span: 200 kHz
VBW: 5 Hz
SWT: 195 s
Fc= 1300 MHz
M2: -41 kHz/-76dB
M2: +41kHz/-75dB



Forschungszentrum
Dresden Rossendorf

SPURIOUS SIGNALS (20kHz)




Pout=8 kW
Source: SMR20
R&S:FSQ26
Span: 20 kHz
VBW: 1 Hz
SWT: 195 s
Fc= 1300 MHz



Forschungszentrum
Dresden Rossendorf

simulation of failure, one slice disconnected



Forschungszentrum
Dresden Rossendorf

GAIN and PHASE CHANGE vs POWER SUPPLY VOLTAGE

sensitivity to voltage changes measured at
different power levels

	2kW	4.6kW	8.5kW	9.1kW
$\Delta\text{gain}/\Delta V$	0.01dB/V	0.01dB/V	0.08dB/V	0.06dB/V
$\Delta\text{phase}/\Delta V$	0.08°/V	0.25°/V	1°/V	0.6°/V



Forschungszentrum
Dresden Rossendorf

SAFETY AND CONTROL

- control system monitors forward and reflected power in real time


- control of : peak power, duty cycle, pulse width and mismatch

- user defined peak power, duty cycle, pulse width and mismatch limits


- control of all individual transistor currents

- control of water flow rate

- control of power modules temperatures



OPERATION AT ELBE



Forschungszentrum
Dresden Rossendorf


OPERATION AT ELBE

- Routine OP : 08.Feb. to 30.Apr.2010
- No failures
- Regimes of operation:
 - CW (FEL, Cavity C4: 8MV/m/ 0.7 mA)
 - Raise-/Fall time sufficient to run macropulse mode (0.1ms/40ms)
 - Ok for single pulse mode
 - Pulse Mode (cavity training)



Forschungszentrum
Dresden Rossendorf


ELBE UPGRADE



Forschungszentrum
Dresden Rossendorf


Block Diagram

RF-POWER (1dB reserve below -1dB comp.: +71 dBm = 12,6 kW
(LIMIT: (each amp.8,5 kW): 72,3dBm-0,3dB= 15,58 kW



Forschungszentrum
Dresden Rossendorf

ELBE UPGRADE



Forschungszentrum
Dresden Rossendorf



Thanks for the excellent cooperation !



Forschungszentrum
Dresden Rossendorf

FWKE • Dr.-Ing. H.Büttig • www.fzd.de • Mitglied der Leibniz-Gemeinschaft