



**A better mitigation of the output noise was suggested by the Gas Group, it consists in the movement of the pulses generators as far as possible from the chambers**



The Output pressure regulator in each Racks has to be moved in USA Gas Room

The change will be tested in one Rack at beginning of LS2 with the present spare manifold for a precise evaluation of the noise improvement.

# New 4 Racks to minimize the pressure inside the chambers



- ✓ The solution is to increase the vertical partition
- ✓ Less  $\Delta p$  = less leaks
- ✓ Additional 4 new Racks expected in LS2 also useful for the BI project in phase2
- ✓ 56 out 128 manifold to be moved to the new Racks

Due to the hydrostatic column [0.3mb/m] of the RPCs Gas Mixture 4 new Racks will be added at present system for a better pressure equalization.

# Manifold to be moved to the new Racks

Rack 61	Ch 1	BOL11A.Ly0	move to	Rack 61.5
Rack 61	Ch 2	BOL11A.Ly1	move to	Rack 61.5
Rack 61	Ch 3	BOL11C.Ly0	move to	Rack 61.5
Rack 61	Ch 4	BOL11C.Ly1	move to	Rack 61.5
Rack 61	Ch 9	BMS12.Ly0	move to	Rack 61.5
Rack 61	Ch 10	BMS12.Ly1	move to	Rack 61.5
Rack 61	Ch 11	BMS12.Ly0	move to	Rack 61.5
Rack 61	Ch 12	BMS12.Ly1	move to	Rack 61.5
Rack 61	Ch 17	BML13.Ly0	move to	Rack 61.5
Rack 61	Ch 18	BML13.Ly1	move to	Rack 61.5
Rack 61	Ch 19	BML13.Ly0	move to	Rack 61.5
Rack 61	Ch 20	BML13.Ly1	move to	Rack 61.5
Rack 61	Ch 25	BMS14.Ly0	move to	Rack 61.5
Rack 61	Ch 26	BMS14.Ly1	move to	Rack 61.5
Rack 61	Ch 27	BMS14.Ly0	move to	Rack 61.5
Rack 61	Ch 28	BMS14.Ly1	move to	Rack 61.5
Rack 61	Ch 29	BOL15A.Ly0	move to	Rack 61.5
Rack 61	Ch 30	BOL15A.Ly1	move to	Rack 61.5
Rack 61	Ch 31	BOL15C.Ly0	move to	Rack 61.5
Rack 61	Ch 32	BOL15C.Ly1	move to	Rack 61.5
Rack 62	Ch 1	BOS16A.Ly0	move to	Rack 62.5
Rack 62	Ch 2	BOS16A.Ly1	move to	Rack 62.5
Rack 62	Ch 3	BOS16C.Ly0	move to	Rack 62.5
Rack 62	Ch 4	BOS16C.Ly1	move to	Rack 62.5
Rack 62	Ch 5	BMS16.Ly0	move to	Rack 62.5
Rack 62	Ch 6	BMS16.Ly1	move to	Rack 62.5
Rack 62	Ch 7	BMS16.Ly0	move to	Rack 62.5
Rack 62	Ch 8	BMS16.Ly1	move to	Rack 62.5
Rack 62	Ch 17	BMS10.Ly0	move to	Rack 62.5
Rack 62	Ch 18	BMS10.Ly1	move to	Rack 62.5
Rack 62	Ch 19	BMS10.Ly0	move to	Rack 62.5
Rack 62	Ch 20	BMS10.Ly1	move to	Rack 62.5
Rack 62	Ch 21	BOS10A.Ly0	move to	Rack 62.5
Rack 62	Ch 22	BOS10A.Ly1	move to	Rack 62.5
Rack 62	Ch 23	BOS10C.Ly0	move to	Rack 62.5
Rack 62	Ch 24	BOS10C.Ly1	move to	Rack 62.5


Rack 64	Ch 1	BOS2A.Ly0	move to	Rack 63.5
Rack 64	Ch 2	BOS2A.Ly1	move to	Rack 63.5
Rack 64	Ch 3	BOS2C.Ly0	move to	Rack 63.5
Rack 64	Ch 4	BOS2C.Ly1	move to	Rack 63.5
Rack 64	Ch 5	BMS2.Ly0	move to	Rack 63.5
Rack 64	Ch 6	BMS2.Ly1	move to	Rack 63.5
Rack 64	Ch 7	BMS2.Ly0	move to	Rack 63.5
Rack 64	Ch 8	BMS2.Ly1	move to	Rack 63.5
Rack 64	Ch 18	BMS8.Ly0	move to	Rack 63.5
Rack 64	Ch 18	BMS8.Ly1	move to	Rack 63.5
Rack 64	Ch 19	BMS8.Ly0	move to	Rack 63.5
Rack 64	Ch 20	BMS8.Ly1	move to	Rack 63.5
Rack 64	Ch 21	BOS8A.Ly0	move to	Rack 63.5
Rack 64	Ch 22	BOS8A.Ly1	move to	Rack 63.5
Rack 64	Ch 23	BOS8C.Ly0	move to	Rack 63.5
Rack 64	Ch 24	BOS8C.Ly1	move to	Rack 63.5
Rack 65	Ch 1	BOL3A.Ly0	move to	Rack 64.5
Rack 65	Ch 2	BOL3A.Ly1	move to	Rack 64.5
Rack 65	Ch 3	BOL3C.Ly0	move to	Rack 64.5
Rack 65	Ch 4	BOL3C.Ly1	move to	Rack 64.5
Rack 65	Ch 9	BMS4.Ly0	move to	Rack 64.5
Rack 65	Ch 10	BMS4.Ly1	move to	Rack 64.5
Rack 65	Ch 11	BMS4.Ly0	move to	Rack 64.5
Rack 65	Ch 12	BMS4.Ly1	move to	Rack 64.5
Rack 65	Ch 17	BML5.Ly0	move to	Rack 64.5
Rack 65	Ch 18	BML5.Ly1	move to	Rack 64.5
Rack 65	Ch 19	BML5.Ly0	move to	Rack 64.5
Rack 65	Ch 20	BML5.Ly1	move to	Rack 64.5
Rack 65	Ch 29	BOL7A.Ly0	move to	Rack 64.5
Rack 65	Ch 30	BOL7A.Ly1	move to	Rack 64.5
Rack 65	Ch 31	BOL7C.Ly0	move to	Rack 64.5
Rack 65	Ch 32	BOL7C.Ly1	move to	Rack 64.5

OLD VERSION

The Rack 63 is unchanged because is connected only to vertical chamber. In the Racks 62, 62.5, 63, 63.5, 64 will be connected in phase 2 to the new 48 manifold for the BI project

# Present system

- Rack65
- Rack64
- Rack63
- Rack62
- Rack61



# Future upgrade

- New Rack 65.5
- New Rack 64.5
- New Rack 61.5
- New Rack 60.5
- Rack65
- Rack64
- Rack63
- Rack62
- Rack61

# Manifold to be moved to the new Racks

RACK 60.5

Ch	From	Label
1	Rack 61_ch5	BOSA12.Ly0.DP1
2	Rack 61_ch6	BOSA12.Ly1.DP2
3	Rack 61_ch7	BOSC12.Ly0.DP1
4	Rack 61_ch8	BOSC12.Ly1.DP2
5	Rack 61_ch13	BOLA13.Ly0.DP2
6	Rack 61_ch14	BOLA13.Ly1.DP1
7	Rack 61_ch15	BOLC13.Ly0.DP2
8	Rack 61_ch16	BOLC13.Ly1.DP1
9	Rack 61_ch21	BOSA14.Ly0.DP1
10	Rack 61_ch22	BOSA14.Ly1.DP2
11	Rack 61_ch23	BOSC14.Ly0.DP1
12	Rack 61_ch24	BOSC14.Ly1.DP2
13	empty	
14	empty	
15	empty	
16	empty	
17	empty	
18	empty	

RACK 61.5

Ch	From	Label
1	BML15.Ly0.DP2	Rack 62_ch9
2	BML15.Ly1.DP1	Rack 62_ch10
3	BML15.Ly0.DP2	Rack 62_ch11
4	BML15.Ly1.DP1	Rack 62_ch12
5	BML11.Ly0.DP2	Rack 62_ch13
6	BML11.Ly1.DP1	Rack 62_ch14
7	BML11.Ly0.DP2	Rack 62_ch15
8	BML11.Ly1.DP1	Rack 62_ch16
9	BI sect. 12	
10		
11	BI sect. 13	
12		
13	BI sect. 14	
14		
15		
16		
17		
18		

RACK 64.5

Ch	From	Label
1	BML3.Ly0.DP2	Rack 64_ch9
2	BML3.Ly1.DP1	Rack 64_ch10
3	BML3.Ly0.DP2	Rack 64_ch11
4	BML3.Ly1.DP1	Rack 64_ch12
5	BML7.Ly0.DP2	Rack 64_ch13
6	BML7.Ly1.DP1	Rack 64_ch14
7	BML7.Ly0.DP2	Rack 64_ch15
8	BML7.Ly1.DP1	Rack 64_ch16
9	BI sect. 3	
10		
11	BI sect. 4	
12		
13	BI sect. 5	
14		
15	BI sect. 6	
16		
17	BI sect. 7	
18		

RACK 65.5

Ch	From	Label
1	BOSA4.Ly0.DP1	Rack 65_ch5
2	BOSA4.Ly1.DP2	Rack 65_ch6
3	BOSC4.Ly0.DP1	Rack 65_ch7
4	BOSC4.Ly1.DP2	Rack 65_ch8
5	BOLA5.Ly0.DP2	Rack 65_ch13
6	BOLA5.Ly1.DP1	Rack 65_ch14
7	BOLC5.Ly0.DP2	Rack 65_ch15
8	BOLC5.Ly1.DP1	Rack 65_ch16
9	BOSA6.Ly0.DP1	Rack 65_ch25
10	BOSA6.Ly1.DP2	Rack 65_ch26
11	BOSC6.Ly0.DP1	Rack 65_ch27
12	BOSC6.Ly1.DP2	Rack 65_ch28
13	empty	
14	empty	
15	empty	
16	empty	
17	empty	
18	empty	

With the new Rack will be available the connections points for the phase 2 RPCs BI project installed at least 2 for sector.

In the space left by the removed manifold in the Racks 62, 63, 64 will be connected the remaining 18 BI channel.

# Summary of Gas System upgrades costs

ISSUE	UPGRADE		Responsibility		TOT. kCHF
Shockwave	Regulation valves move from UX to USA	New Rack in USA	Gas Group		75
		Pipe from UX to USA	Atlas TC	To be evaluated	?
Chamber pressure lowering	4 new Racks	Racks	Gas Group	75 KCHF x4	300
		Pipe movement between Racks x56	TC + Muon RPC	To be evaluated	?
O <sub>2</sub> sensor	New Analysis "module" in USA/SGX1 for RPC				25
<b>Total</b>					<b>400</b>

# About LS2 inert humidified gas circulation

## □ From TFE to inert at fixed pressure

The chambers Flow will be set by the Input pressure controlled by Hagen-Poiseuille law

$$\Delta P = \frac{8\mu L}{\pi r^4} \phi$$

$$\Delta P_{Ar} = 2.54$$

$$\Delta P_{TFE} = 1.57$$

$$\Delta P_{Air} = 2.05$$

$$\Delta P_{CO_2} = 1.67$$

$$(@ L=1m; r=1mm \phi = 1 \frac{l}{h})$$

$$@ \text{ fixed } P \quad 2.54 \phi_{Ar} = 1.57 \phi_{TFE} \quad \phi_{Ar} = 0.61 \phi_{TFE} \quad \phi_{Air} = 0.76 \phi_{TFE}$$

□ At fixed pressure higher flow with Air or Nitrogen than Ar



# About LS2 inert humidified gas circulation

## □ Thermal Gas Mass Flow Meters sensitivity from TFE to inert

	K relative to N <sub>2</sub>	Cp (Cal/g)	Density (g/l)
TFE C <sub>2</sub> H <sub>2</sub> F <sub>4</sub>	.51	.127	4.22
Air or Nitrogen	1	.24	1.29
Ar	1.45	1.24	1.78
CO <sub>2</sub>	.74	0.20	1.96

$$Q_{Ar} = \frac{K_{Ar}}{K_{TFE}} Q_{TFE}$$

$$Q_{Ar} = 2.58 Q_{TFE}$$

$$Q_{Air} = 1.96 Q_{TFE}$$

## □ At fixed pressure higher flow with Air or Nitrogen than Ar

$$K_{gas} = \frac{1}{d \times C_p}$$

where d = gas density (gram/liter)

C<sub>p</sub> = coefficient of specific heat (cal/gram)

$$K = \frac{Q_a}{Q_r} = \frac{K_a}{K_r}$$

where Q<sub>a</sub> = mass flow rate of an actual gas (sccm)

Q<sub>r</sub> = mass flow rate of a reference gas (sccm)

K<sub>a</sub> = K factor of an actual gas

K<sub>r</sub> = K factor of a reference gas