



Updated
06-08-2018

Reference situation of cooling capabilities for 11T and implications for eventual modification (needs and impact)

Rob van Weelderen,
Serge Claudet,
Mario David Grosso Xavier,
Kirtana Puthran

+ multiple inputs from the Fluka
& Collimation teams




54th TCC 02/08/2018

Overview

- Intro
- 11 T dipole thermal quench limit
- 11 T dipole steady-state cooling limits
 - Coil + beam-pipe
 - Cold-mass
- DS – cryogenic hardware steady-state cooling limits
- Cryogenic assessment summary
- Implications for proposed Beam-Lifetime scenarios
- Summary

Intro

Assesment on various scales of the thermal load withstand-levels of the 11T-dipole and the DS-cells



11 T dipole thermal quench limit

The thermal quench limits as function of locally deposited power are assessed via:

- 1) Thermal characterization of cut-out coil **stack-sample** in cryolab-test stand
- 2) **Computational Fluid Dynamics** of coil-section using inputs from (1) + material data

2) Thermal relaxation times

Experimental setup




Exploiting different AC loss mechanisms the sample is heated and the temperature evolution in sample and bath is measured.

The generated power can be varied by changing the combination of the resistor box.

Important parameters:

T_{eq} : equilibrium temperature


τ : time constant (time to reach 63.2 % of peak temperature)



Cryostat

2) Thermal relaxation times

WARNING: Uniform power deposition results CANNOT be simply translated to 11 T Dipole loss profile




11 T dipole thermal quench limit

Steady state modelisation results

(by former fellow *Fouad Aabid*)

11-Tesla Dipole



Mesh Quality:

Numerical Mesh: 375196 cells (hexahedral)

Min. cell volume: $6.2\text{e-}12 \text{ m}^3$ – Max. cell volume: $8.8\text{e-}9 \text{ m}^3$

99% of Mesh Cells < 0.5 in Equisize Skewness, worst element at 0.83

Boundary Conditions:

Constant Temperature $T=1.9\text{K}$ at the Cold Source


Adiabatic Walls (No heat exchange) on the walls of the External Shell

Uniform heat flux from the Coldbore (where peak power density is): 3.31 W.m^{-3}


Steady state modelisation results 11T-dipole

(by former fellow *Fouad Aabid*)

11-Tesla Dipole



Lowest Temperature Margin
 ≈ 3.58 K



The temperature margin is largely above the limit of quenching.

11 T dipole thermal quench limit

Steady state modelisation results 11T-dipole

(by former fellow *Fouad Aabid*)

Recap:

At 32 mW/cm³ → Tmargin ~ 3.6 K

At 50 mW/cm³ → Tmargin ~ 3.0 K

At 100 mW/cm³ → Tmargin ~ 1.9 K

Locally the 11T dipole coil is *can take high heating loads*.

However these values apply only to the worst cold-mass coil-section!

Whether the loads can be sustained over large cold-mass volumes and multiple magnets and as function of time depends on the previous DS cooling capacity assessment for Proton and Ion runs respectively


Complementary validation is ongoing with Cryolab stack-measurements analysis

(Note: strong indications of some He presence in coil pack, to be confirmed)

11 T dipole steady state as function of power:

1) « static coil + beam-pipe cooling limits »


Coil-heat must go **first** from **coil to annular space** around beam-pipe and then towards the **magnet ends**



11 T dipole steady state as function of power:

1) « static coil + beam-pipe cooling limits »

Continuously extractable power from 11T – coils + beam – pipe




Without radial cooling channels the total continuous extraction capacity limit from the coil area ranges from $\approx [50 \text{ W @ } 1.95 \text{ K} - 15 \text{ W @ } 2.10 \text{ K}]$ (both apertures combined)

Steady state as function of power:

2) « cold-mass cooling limits »

If we consider that the DS-bayonet heat exchanger is operated at its fullest capacity then the 11T cold-mass part will take $\approx 8\text{-}10\text{ W}$ under the corresponding ΔP and wetting conditions. The remainder is conducted away.

Neighbouring magnets can then take $\approx 50\text{ W}$ max, hardware limited by the cold-mass interconnects' free conduction area within limited ΔT .



→ **total $\approx 60\text{ W}$** for the full 11T cold –mass
(i.e. coil + collars + yoke + beam pipe +...)

Precise profile to be evaluated with detailed model

Implications for proposed Beam-Lifetime scenarios

Detailed data for cryogenics analysis

All the following plots and provided data are for:

- TCLD and 11T replacing **MBB.B8** (IR7)
- The **most exposed 11T** out of the two modules: downstream from TCLD

Beam LifeTime (BLT) of 1 h is just a rescaling of the 0.2h BLT results (0.2h results divided by 5).

BLT of 0.2 hours, considers: Ions: 1248 bunches $2.1e8$ ions/bunch. **Protons:** 2760b $2.3e11$ p / bunch

Previous benchmarks showed a **factor 3** underestimation in DS with respect to BLM measurements: **this factor is already accounted for in the data.**


21/06/18

C. Bahamonde - WP 11 Technical machine interfaces working group

1

Courtesy Cristina Bahamonde Castro

Implications for proposed Beam-Lifetime scenarios




Courtesy Cristina Bahamonde Castro

→ Protons: 11 mW/cm³ keeps > 3.6 K temperature margin according to CFD-model

Implications for proposed Beam-Lifetime scenarios

Radially averaged peak power inner coils: most exposed 11T in cell 8 (Ions)



Courtesy Cristina Bahamonde Castro

→ Ions: 21 mW/cm³ keeps > 3.6 K temperature margin
according to CFD-model

Implications for proposed Beam-Lifetime scenarios

Heat load to the cold mass part by part

| Heat load to the cold mass for HL-LHC most exposed 11T of cell 8 (W) | | | | |
|--|---------------------|------------------|---------------------|------------------|
| | PROTONS | | IONS | |
| | <i>BLT (12 min)</i> | <i>BLT (1 h)</i> | <i>BLT (12 min)</i> | <i>BLT (1 h)</i> |
| Coils (return coils included) | 54 | 11 | 98 | 20 |
| Yoke | 44 | 9 | 85 | 17 |
| Collars | 32 | 6 | 62 | 12 |
| Spacers (between coils) | 11 | 2 | 23 | 5 |
| Vacuum vessel | 4 | 1 | 7 | 1 |
| Beam pipe | 4 | 1 | 7 | 1 |
| Shrinking cylinder | 2 | 0.4 | 4 | 1 |
| Other parts | 19 | 4 | 44 | 9 |
| TOTAL | 170 | 34 | 330 | 66 |

C. Bahamonde - WP 11 Technical machine interfaces working group

2

Courtesy Cristina Bahamonde Castro

→ Protons: coil + beam-pipe 12 W (BLT 1h) , total 34 W
Ions.....: coil + beam-pipe 21 W (BLT 1h), total 66 W

Intermediate 11T dipole specific summary for proposed beam-Lifetime scenarios (MBB.B8)

Continuous cooling \leftrightarrow Blt 1h

| | Peak power (mW/cm ³) | 11T: coil + beam-pipe (W) | 11T total (W) | comment |
|---------|-------------------------------------|---------------------------------|------------------|--|
| Protons | 2 | 12 | 34 | & (< 50 mW/cm ³ and < 41 W, total < 60 W) |
| Ions | 4 | 21 | 66 | & (< 50 mW/cm ³ and < 41 W total close to 60 W) |

For the 1h Blt the 11T dipole thermal design is sufficient


Intermediate 11T dipole specific summary for proposed beam-Lifetime scenarios (MBB.B8)

Transient cooling \leftrightarrow Blt 12min

| | Peak power (mW/cm ³) | 11T: coil + beam-pipe (W) | 11T total (W) | 10 s Energy (kJ)/(kJ/m) | comment |
|---------|-------------------------------------|---------------------------------|------------------|-------------------------------|--|
| Protons | 11 | 58 | 170 | 1.7/0.3 | < 50 mW/cm ³ coil > 40 W, total > 60 W |
| Ions | 21 | 105 | 330 | 3.3/0.6 | < 50 mW/cm ³ coil > 40 W, total > 60 W |

For the 12min Blt the 11T dipole thermal design is ok for peak power on coil - but overall temperature will drift during transient

DS - cryo hardware steady-state cooling limits



Generically **LHC-cell** cooling-power provided by the collective performance of:

1. Bayonet heat exchanger, *protruding through all cold masses*: **design limit 7 g/s $\equiv 140 \text{ W}$** (at 1.9 K, pumping)
2. Very low pressure counterflow heat exchanger *installed in the QRL-service module*: **limit 5 g/s $\equiv 100 \text{ W}$** (at 1.9 K, pumping)
3. Every 2nd **LHC-cell**, cooling exchange between cells is **blocked** by hydraulic restrictions.

DS - cryo hardware steady-state cooling limits

Proton run !

77 W

+ ≤ 77 W

Q7 MB 11T TC LD 11T MB Q8 MB MB Q9 MB MB Q10 MB MB LE Q11 plug MB ...

| Proton run | ½-Cell 8+9 (W) | Redundancy - ½ -Cells 10+11 (W) |
|-------------------------------|----------------|--|
| static + splices (0.25 W/m *) | 23 | 23 |
| beam-gas (0.0 W/m *) | 0 | 0 |
| Total (0.25 W/m) | 23 | 23 |
| Available for collimation | 77 | ≤ 77 (some loss due to conduction to be expected) |

- Loss data from CERN-ATS-2010-016
- considering beam-gas based on present LHC vacuum (factor 200 lower than TDR)


→ Cell 8 has **77 W** available for collimation loads, *all magnets combined!*
 → Some extra load ≤ 77 W could be taken via conduction through the neighbouring cell-9 cooling, *if all loads would be < 200 W total* (see later on).

DS - cryo hardware steady-state cooling limits

Ion run !

77 W

+ ≤ 77 W



| Ion run | Cell 8 (W) | Redundancy - Cell 9 (W) |
|-------------------------------|------------|--|
| static + splices (0.25 W/m *) | 23 | 23 |
| beam-gas (0 W/m *) | 0 | 0 |
| Total (0.25 W/m) | 23 | 23 |
| Available for collimation | 77 | ≤ 77 (some loss due to conduction to be expected) |

- Loss data from CERN-ATS-2010-016
- considering beam-gas based on present LHC vacuum (factor 200 lower than TDR)

→ Cell 8 has **77 W** available for collimation loads, *all magnets combined!*
 → Some extra load ≤ 77 W could be taken via conduction through the neighbouring cell-9 cooling, *if all loads would be < 200 W total* (see later on)

Implications for proposed beam-life scenarios

- LHC operating experience puts the DS-helium temperatures ≤ 1.95 K
- → We aim to keep the 11T helium at **1.95 K**
- → This is **only possible** for **total loads** not exceeding the **2x100 W limit** of neighbouring cooling-loops
- → The exceptions are high **short – time** losses when the helium **temperature will drift** as the heat gets absorbed.


DS - cryo hardware steady-state cooling limits

Proton run !

Loss data Fluka team, 1h life time

$$23 \text{ W} + 42 \text{ W} + 20 \text{ W} = 85 \text{ W}$$

$$23 \text{ W} + 2 \text{ W} + (63-70) \text{ W} = 88 - 95 \text{ W}$$



Total loads are < 200 W → Cryo-infrastructure can maintain this in steady state!


DS - cryo hardware steady-state cooling limits

Proton run !

Loss data Fluka team, **12min** life time

$$23 \text{ W} + 210 \text{ W} + 100 \text{ W} = 333 \text{ W}$$

$$23 \text{ W} + 10 \text{ W} + (315-350) \text{ W} = 348 - 383 \text{ W}$$



Total loads are $\gg 200 \text{ W}$ \rightarrow Cryo-infrastructure cannot maintain this in steady state!

The heat capacity of the DS-helium content will have to be used!


DS - cryo hardware steady-state cooling limits

Ion run !

Loss data Fluka team, **1h** life-time

$$23 \text{ W} + 70 \text{ W} + 27 \text{ W} = 120 \text{ W}$$

$$23 \text{ W} + 4 \text{ W} + (135-150) \text{ W} = 162 - 177 \text{ W}$$



Total loads are > 200 W → Cryo-infrastructure **cannot maintain this in steady state!**

The heat capacity of the DS-helium content will have to be used!


DS - cryo hardware steady-state cooling limits

Ion run !

Loss data Fluka team, **12min** life-time

$$23 \text{ W} + 350 \text{ W} + 135 \text{ W} = 508 \text{ W}$$

$$23 \text{ W} + 20 \text{ W} + (675-750) \text{ W} = 718 - 793 \text{ W}$$




Total loads are $\gg 200 \text{ W}$ \rightarrow Cryo-infrastructure cannot maintain this in steady state!

The heat capacity of the DS-helium content will have to be used!

DS - cryo hardware steady-state cooling limits

heating of the DS – cells 8 and 9 : helium starting at 1.95K




Protons (1hr Blt) : The **12 W** which need to be extracted from the coil+beam-pipe area can be sustained continuously

Ions (1hr Blt): The **21 W** which need to be extracted from the coil+beam-pipe area is reached after **>> 60 min**

DS - cryo hardware steady-state cooling limits

heating of the DS – cells 8 and 9 : helium starting at 1.95K




Protons (12min Blt) : The **58 W** which need to be extracted from the coil+beam-pipe area **cannot be taken by the helium at 1.95 K** → **Adiabatic T-rise of coil** (to be evaluated)

Ions (12min Blt): The **105 W** which need to be extracted from the coil+beam-pipe area **cannot be taken by the helium at 1.95 K** → **Adiabatic T-rise of coil** (to be evaluated)

DS - cryo hardware steady-state cooling limits

heating of the DS – cells 10 and 11 : helium starting at 1.95K



Ions (1hr Blt) : The MB dipole limits in cells 10 & 11 will see the above given T vs time, **worse than cells 8 & 9.**

The MB dipole functioning limits under these conditions have to be ascertained.

Summary

11-T dipole design:

No radial cooling holes necessary to deal with coil+beam-pipe heat loads

Cryogenic-limitations:

1hr Blt: cooling of 11-T-dipole ok for Protons and for Ions

1hr Blt: cooling of cells 10 & 11 MB-dipoles ok for Protons

1hr Blt: cooling of cells 10 & 11 MB-dipoles could be critical for Ions

12min Blt: helium cooling not effective

→ adiabatic T-rise of 11-T-dipole coil (to be evaluated)

→ propose power limit test in LHC