



Contribution ID: 88

Type: **not specified**

# Robust Cs<sub>2</sub>Te and Mg photocathodes in SRF gun at ELBE center successful for CW IR FEL and THz radiation

*Tuesday, 16 October 2018 17:25 (20 minutes)*

Quality of photocathodes is one of the critical issues for the stability and reliability of the light source facility. In 2014, SRF gun-I with Cs<sub>2</sub>Te provided stable electron beams successfully for IR FEL at HZDR [1]. Cs<sub>2</sub>Te worked in SRF gun for more than one year without degradation. Currently, Mg photocathodes with QE up to 0.5% are applied in SRF Gun II, which is able to generate e<sup>-</sup> beam with bunch charges up to 200 pC in CW mode with sub-ps bunch length for the high power THz radiation facility for the ELBE users [2].

1. J. Teichert et al., Free-electron laser operation with a superconducting radio-frequency photoinjector at ELBE, Nuclear Instruments and Methods in Physics Research A 743 (2014) 114-120
2. Xiang et al., Study of Magnesium Photocathodes for Superconducting RF Photoinjectors, IPAC 2018, Vancouver, Canada, April 29 –May 4, 2018

**Presenter:** XIANG, rong (Helmholtz-Zentrum Dresden-Rossendorf)

**Session Classification:** Session 8

**Track Classification:** Session 8: Operations and Demonstrations - Superconducting & DC