



Contribution ID: 1121

Type: **Invited Oral Presentation**

## **M3Or3A-04 [Invited]: Process for scalable fabrication of low AC loss HTS conductors**

*Wednesday, July 24, 2019 3:30 PM (30 minutes)*

A scalable process has been developed to fabricate low AC loss cable from second generation high temperature superconducting (2G HTS) coated conductors with an emulated Rutherford twisted conductor topology. The process uses an indexed tape design to precisely align separate YBCO tapes to form a single tape structure making it compatible with a reel-to-reel production process and involves a combination of three methods: (1) the use of laser lithography to striate 2G HTS tapes into a pattern of isolated diagonal filaments, (2) the precise alignment and decal bonding of a pattern of solder preforms to the filament edge contact areas, and (3) the alignment and bonding of a top and bottom HTS tape with a thin intervening adhesive layer that provides mechanical adhesion and electrical isolation between adjacent bonds and the interior where filament transposition occurs. The observation of a resistive critical current transition in the fully fabricated transposed striated HTS conductor indicates that all bonds were well formed and the superconducting current path was restricted to the filaments.

**Authors:** PRESTIGIACOMO, Joseph (US Naval Research Laboratory); Mr AUYEUNG, Raymond (US Naval Research Laboratory); Dr OSOFSKY, Michael (US Naval Research Laboratory)

**Presenter:** PRESTIGIACOMO, Joseph (US Naval Research Laboratory)

**Session Classification:** M3Or3A - Transportation Symposium: Transportation Cables