



Contribution ID: 683

Type: **Contributed Oral Presentation**

## **C3Or2B-02: Simulation of a cryogenic capillary tube: thermodynamic behavior subjected to heat load.**

*Wednesday, July 24, 2019 2:30 PM (15 minutes)*

Pulsating Heat Pipes (PHP) are excellent heat transfer devices, constituting the thermal link between a cold sink and an object to cool. The interest for developing cryogenic pulsating heat pipes to cool superconducting magnets is growing because of their lightness and high thermal performance. A numerical model has been developed using the Navier-Stokes solver from ANSYS Fluent software to evaluate the influence of different parameters affecting the thermodynamic behavior of cryogenic working fluids in the pulsating heat pipes. An existing experiment of a single horizontal capillary tube is reproduced in the simulation where the two-phase operating fluid is computed using the VOF method in a 2D axisymmetric mesh. Different parameters are tested to analyze the liquid-vapor interface and the heat transfer between the wall and the two-phase fluid in order to contribute to a better understanding of the working fluid behavior and to the development of future 2D simulations of pulsating heat pipes.

**Primary author:** BARBA, Maria (CEA (Commissariat à l'Énergie Atomique))

**Co-authors:** BRUCE, Romain (CEA Saclay); BAUDOUY, Bertrand (CEA Saclay)

**Presenter:** BARBA, Maria (CEA (Commissariat à l'Énergie Atomique))

**Session Classification:** C3Or2B - Thermal-Fluid Transport and Properties for Fluids Boiling Above 50 K