



Contribution ID: 625

Type: **Poster Presentation**

M1Po2D-01 [45]: DC Surface Flashover Characteristics of ZnO/EP Composites at 77K

Monday, 22 July 2019 14:00 (2 hours)

Epoxy resin nanocomposites are widely used in high voltage direct current (HVDC) high temperature superconducting (HTS) power cable. In this paper, the DC flashover characteristics of ZnO/EP composites at both room temperature and 77K were studied. The samples were made by dispersing ZnO nanoparticles into EP resin with weight percentages of 0%, 1%, 3%, 6% and 10% respectively. The experiment was carried out under a cryogenic system in which DC high voltages ranging from 0kV to 100kV were supplied. The results show that the surface flashover voltages changed with the increase of ZnO content at 77K, and the surface flashover voltages at 77K were higher than that at room temperature for composites with the same ZnO content.

Primary author: ZHANG, Kaikai (Key Laboratory of Cryogenics, Technical Institute of Physics and Chemistry, CAS and Center of Materials Science and Optoelectronics Engineering, University of Chinese Academy of Sciences)

Co-authors: HUANG, Rongjin (Key Laboratory of Cryogenics, Technical Institute of Physics and Chemistry, CAS and Center of Materials Science and Optoelectronics Engineering, University of Chinese Academy of Sciences); WANG, Yongguang (Key Laboratory of Cryogenics, Technical Institute of Physics and Chemistry, CAS and Center of Materials Science and Optoelectronics Engineering, University of Chinese Academy of Sciences); LI, Jian (Key Laboratory of Cryogenics, Technical Institute of Physics and Chemistry, CAS and Center of Materials Science and Optoelectronics Engineering, University of Chinese Academy of Sciences); ZHANG, Hua (Key Laboratory of Cryogenics, Technical Institute of Physics and Chemistry, CAS and Center of Materials Science and Optoelectronics Engineering, University of Chinese Academy of Sciences); ZHANG, Chi (Key Laboratory of Cryogenics, Technical Institute of Physics and Chemistry, CAS and Center of Materials Science and Optoelectronics Engineering, University of Chinese Academy of Sciences); LIU, Huiming (Key Laboratory of Cryogenics, Technical Institute of Physics and Chemistry, CAS); XU, Dong (Key Laboratory of Cryogenics, Technical Institute of Physics and Chemistry, CAS); HUANG, Chuanjun (Key Laboratory of Cryogenics, Technical Institute of Physics and Chemistry, CAS); LI, Laifeng (Key Laboratory of Cryogenics, Technical Institute of Physics and Chemistry, CAS and Center of Materials Science and Optoelectronics Engineering, University of Chinese Academy of Sciences)

Presenter: ZHANG, Kaikai (Key Laboratory of Cryogenics, Technical Institute of Physics and Chemistry, CAS and Center of Materials Science and Optoelectronics Engineering, University of Chinese Academy of Sciences)

Session Classification: M1Po2D - Thermal, Electrical, and Magnetic Materials Properties