



Contribution ID: 727

Type: **Poster Presentation**

## **C1Po1C-02 [04]: Wide temperature range test of high capacity Stirling cryocooler**

*Monday 22 July 2019 09:00 (2 hours)*

This paper describes the cooling performance test of a free piston Stirling cryocooler accompanied by a double acting linear compressor. Although, the aforementioned Stirling cryocooler had originally been subjected to 77 K applications, i.e. liquid nitrogen (LN<sub>2</sub>), in this research, we have tried to figure out the cooling performance of the Stirling cryocooler operating above-110 K temperature range. The relevant targets are as the follows, i.e. high temperature superconducting (HTS), liquid natural gas (LNG) re-liquefaction and industrial ultra-low freezer applications. During the experiments, the instantaneous pressures, displacement of the piston and the displacer, current and voltage have been acquired as the cold-end temperature varied from 110 K to 190 K. The Stirling cryocooler has recorded the Carnot COP to be 25%, 27%, 28% and 29% at the cold-end temperatures of 110 K, 120 K, 150 K and 190 K, respectively. In this research paper, all the physical variables will extensively be analyzed by a 'dynamic model' and the relevant operational issues will also be discussed.

**Authors:** Dr KO, Junseok (Korea Institute of Machinery & Materials); PARK, Jiho (Korea Institute of Machinery and Materials); Dr KIM, Hyobong (Korea Institute of Machinery & Materials); Dr HONG, Yong-Ju Hong (Korea Institute of Machinery & Materials); Dr YEOM, Hankil (Korea Institute of Machinery & Materials); Dr IN, Sehwan (Korea Institute of Machinery & Materials); Dr PARK, Seong-Je (Korea Institute of Machinery & Materials)

**Presenter:** Dr KO, Junseok (Korea Institute of Machinery & Materials)

**Session Classification:** C1Po1C - Stirling and VM Coolers