



Contribution ID: 988

Type: **Poster Presentation**

## **M2Po2C-03 [39]: Trial Manufactures of Jelly-Rolled Nb/Al Single Wire with Very Small Diameter below 50 microns**

*Tuesday, 23 July 2019 13:30 (2 hours)*

In general, practical metallic superconducting wires, such as NbTi, Nb<sub>3</sub>Sn and V<sub>3</sub>Ga, have a fine multifilamentary configuration. Its predominant reason would be pointed as the reduction of electromagnetic losses, the improvement of intrinsic and thermal stabilities, and the reduction of mechanical strain. In particular on the A15 compounds, the promotion of the chemical reaction through the shortening of the diffusion distance would be added to above reason. According to these understandings, so far we have been developing the Nb<sub>3</sub>Al monolith wires having multifilament configuration. However, several R&D issues, such as the wire-breakage of multifilamentary precursors, costly Cu stabilizer fabrication, low mechanical irreversible strain, still remains. On the other hand, we are considering dramatically different approach to fabricate Nb<sub>3</sub>Al superconducting wires of which have low electromagnetic losses, enough intrinsic and thermal stabilities, excellent flexibility for the coil winding through the React & Wind method, and low fabrication cost. It is the braided conductor that a multiplicity very fine single strands are braided into a cylindrical pattern. Especially, the flat dimensionally transposed braided conductor was called "BNL Braid". In this paper, as a first step of new approach, we tried manufactures of Jelly-Rolled Nb/Al single precursor wires having a diameter of less than 50 microns. The drawing workability, microstructure changes, and then superconducting properties after heat treatment of very fine Nb<sub>3</sub>Al single wires were investigated.

**Primary authors:** Dr KIKUCHI, Akihiro (National Institute for Materials Science); Mr IJIMA, Yasuo (National Institute for Materials Science); Mr CHIKATSU, Masayuki (National Institute for Materials Science); Mr YAMADA, Kyohei (National Institute for Materials Science); Dr HIRATA, Kazuto (National Institute for Materials Science); Dr NIMORI, Shigeki (National Institute for Materials Science); Dr TSUCHIYA, Kiyosumi (KEK); Dr ICHINOSE, Ataru (Central Research Institute of Electric Power Industry); Mr KAWANO, Masatoshi (Meiko Futaba Co., Ltd.); Mr YAMAMOTO, Masaru (Meiko Futaba Co., Ltd.); Mr NAGAMATSU, Jun (YUKI Precision Co., Ltd.); Mr KIMURA, Motoyoshi (Meiko Futaba Co., Ltd.); Mr OTSUBO, Masato (YUKI Precision Co., Ltd.)

**Presenter:** Dr KIKUCHI, Akihiro (National Institute for Materials Science)

**Session Classification:** M2Po2C - Nb Properties and A15 Conductor