



Contribution ID: 974

Type: **Poster Presentation**

Wed-Af-Po3.25-06 [110]: Experimental and numerical study on crack evolution of Nb barriers causing I_c deterioration in multi-filament MgB₂ strands during cabling process for large-scale energy storage coils.

Wednesday 25 September 2019 14:00 (2 hours)

MgB₂ strands have been highly developed commercially, providing great interest in superconducting magnetic energy storage (SMES) applications with low cost by using liquid hydrogen (LH₂) as a coolant due to the higher critical temperature compared to the boiling temperature of the LH₂. Therefore, the MgB₂ SMES is promising device, giving us a remarkable synergy effect by combining the stabilization of fluctuated power originated from renewable energy sources and supply of hydrogen gas for developing hydrogen-based society to reduce the carbon foot print. For the applications with large stored energy, the current capacity of MgB₂ conductor should be large for the compensation of the power fluctuations. In this sense, we need to fabricate large scale conductors for making SMES coils with large stored energy. Our group has been investigating the feasibility study of SMES using MgB₂ indirectly cooled by liquid hydrogen. In our investigation, the deterioration in critical current of Rutherford cables has been observed. Cracks in Nb barriers became apparent by measured images of the cross sections of the deformed strands with high-resolution, X-ray source CT, which are considered to be caused by strand bending and/or dents at the strand cross over points during cabling process. To clarify the mechanism of the damage of the strands, numerical simulation based on non-linear extended FEM is also performed. The calculation showed that some overlap points in the Nb barrier covering the MgB₂ powders produced by CTFF method would behave as crack-initiation during loading. The experimental and numerical approach for analyzing deteriorations in superconducting characteristics of MgB₂ strands shown in this report will lead to the further development of large-scale, cost effective storage device which has great potential to increase the electric power generated by uncontrollable energy sources.

Authors: YAGAI, Tsuyoshi (Sophia University); Mr HIRA, Moeto (Sophia University); Mr ONJI, Taiki (Railway Technical Research Institute); Mr KUWABARA, Yusuke (Sophia University); Ms JIMBO, Mana (Sophia University); Mr KAMIBAYASHI, Masahiro (Sophia University); TAKAO, Tomoaki (Sophia University); MAKIDA, Yasuhiro (High Energy Accelerator Research Organization (JP)); SHINTOMI, Takakazu (KEK); Mr KOMAGOME, Toshihiro (Mayekawa MFG. Co., Ltd.); Dr TSUKADA, Kenichi (Mayekawa MFG. Co., Ltd.); Dr HOSHINO, Masayuki (Mayekawa MFG. Co., Ltd.); Dr HIRANO, Naoki (Chubu Electric Power Co., Inc.); TOMITA, Masaru (Railway Technical Research Institute); MIYAGI, Daisuke (Tohoku University); MATSUDA, Hidefumi (kyoto university); TSUDA, Makoto (Tohoku University); Prof. HAMAJIMA, Takataro (Mayekawa MFG. Co., Ltd.)

Presenter: YAGAI, Tsuyoshi (Sophia University)

Session Classification: Wed-Af-Po3.25 - MgB₂ and Iron-Based