

## Layout and Performance of HPK Prototype LGAD sensors for the High-Granularity Timing Detector HGTD

*Saturday, December 14, 2019 3:27 PM (1 minute)*

We report on the layout and performance of Low-Gain Avalanche Detectors (LGAD) produced by HPK as prototypes for the HGTD in ATLAS. The HGTD is a multi-layer upgrade of the ATLAS detector of total area of 6.4m<sup>2</sup> covering the pseudo-rapidity region between 2.4 and 4.0 with timing sensors with time resolution of 50 ps, representing the first large scale application of the LGAD.

With a common mask, sensors with an active thickness of 50  $\mu\text{m}$  (2 splits) and 35  $\mu\text{m}$  (3 splits) were produced. The different splits refer to different combinations of doping profile of the gain layer and resistivity of the bulk, which were measured using C-V. The layout of the sensors is based on a pitch of 1.3 x1.3 mm<sup>2</sup> pads. Single pads with varying distance to the edge and 2x2 arrays with different inter-pad gap were used to determine safe outside and inside dimensions. Large arrays with 5x5 and 15x15 pads were used to investigate the yield by measuring the breakdown voltage. The dynamic properties of the LGAD were determined with charge collection measurements with laser and charged particles yielding the bias dependence of the gain and of the time resolution.

### Submission declaration

Original and unpublished

**Primary authors:** YANG, Xiao (University of Science and Technology of China (CN)); LIU, Yanwen (University of Science and Technology of China (CN))

**Co-authors:** SADROZINSKI, Hartmut (University of California,Santa Cruz (US)); ATLAS HGTD SENSOR COLLABORATION

**Presenters:** YANG, Xiao (University of Science and Technology of China (CN)); LIU, Yanwen (University of Science and Technology of China (CN))

**Session Classification:** POSTER

**Track Classification:** New ideas and future applications