## 12th International "Hiroshima" Symposium on the Development and Application of Semiconductor Tracking Detectors (HSTD12) at Hiroshima, Japan

Contribution ID: 339 Type: ORAL

## New Pixel Detector Concept 'DuTiP' for Belle II Upgrade and the ILC with an SOI Technology

Sunday 15 December 2019 17:00 (20 minutes)

Belle II experiment was successfully started. The first data for physics with full Belle II detector were taken in 2019 and  $50ab^{-1}$  data will be accumulated by 2027. A discussion of an upgrade plan for Belle II and SuperKEKB is started. The instantaneous luminosity by the upgraded SuperKEKB is 5 times larger than current design luminosity for SuperKEKB ( $8x10^{35}cm^{-2}s^{-1}$ ) and the upgraded Belle II will collect data sample of  $250ab^{-1}$ . In such high luminosity environment, current DEPFET pixel detector is hard to operate due to too high occupancy since the readout scheme of DEPFET is rolling shutter mode with a  $20\mu s$  frame.

We have invented a new pixel detector concept 'DuTiP' (Dual Timer Pixel) which is a binary pixel detector with a trigger signal based global shutter readout scheme. A binary hit information is stored in a down counting timer inside a pixel whose initial value is set as trigger latency plus 1 clock (around  $5\mu$ s). If the trigger signal is recieved when the timer is 1 (0 or 2), the hit information is readout as current (previous or next) timing. To take into account for multiple hits during trigger latency, two timers are equipped in a pixel. The clock speed is important parameter for the occupancy and data size . We tentatively decided the clock speed as 15.9MHz (62.9ns). The requirement of spacial resolution at Belle II is around  $10\mu$ m for both z and r-phi directions, thus  $35\mu$ m pixel size is selected. This pixel detector can be also used for layer 7 and 8 of ILC vertex detector which requires single bunch (554ns) time stamping capability and moderate spatial resolution of  $10\mu$ m in r-phi direction.

We report the concept of 'DuTiP' and the status of development of the pixel detector with an SOI technology for Belle II upgrade.

## **Submission declaration**

Original and unpublished

**Co-authors:** ARAI, Yasuo (High Energy Accelerator Research Organization (JP)); HABA, Junji (KEK); Prof. KURACHI, Ikuo (HIgh Energy Accelerator Research Organization); LI, Taohan (Tohoku); ONO, Shun (KEK); Mr TAKAYANAGI, Takehiro (KEK); TAKEDA, Ayaki (University of Miyazaki); TSUBOYAMA, Toru (KEK, High Energy Accelerator Research Organization); YAMADA, Miho (TMCIT)

Session Classification: Session4

Track Classification: Pixel sensors for tracking