



Collimation MPP-related software and settings generation

R. Bruce, A. Mereghetti, S. Redaelli, B. Salvachua Ferrando, M. Solfaroli Camillocci

With relevant input from M. Di Castro and M. Deile

MPP Workshop 2019

May, 7th – 8th 2019

Chateau de Bossey, Bogis-Bossey, VD, Switzerland



Outline

- Introduction
- Settings generation, testing and verification
- Collimator alignment
- XRPs
- Temperature interlocks
- Wish list of changes
- Conclusions


Outline

- Introduction
- Settings generation, testing and verification
- Collimator alignment
- XRPs
- Temperature interlocks
- Wish list of changes
- Conclusions

Overview of the Collimation System


- The multi-stage LHC collimation system is aimed at **reducing risks of quench** from circulating beam in case of regular and abnormal losses;
- **No quenches** from circulating beam recorded during Run II, with up to 300 MJ stored energy and 6.5 (Z) TeV beams (see D. Mirarchi's talk);
- Overall system performance depends critically on **correct collimator positioning** wrt the beam;

System is complex, with >100 movable devices: control functions must be reliably played *at the same time*, with adequate interlocking;



Collimation Positions and Settings


- Jaw positioning is achieved by 4 stepping motors, one per jaw corner;
 - Motors equipped with resolvers and LVDT sensors (Linear Variable Differential Transformer);
 - LSA settings (LHC Application Software): *requiredAbsolutePosition* (sent to the hardware), determined by means of higher level parameters (eg: optics functions, emittance, $N\sigma$, ...);
- Jaw positions determine:
 - Collimator gaps:
 - these are the actual collimator settings desired/required for operation
 - 2 settings: gap upstream and downstream;
 - equipped with LVDTs;
 - Collimator centering and jaw angle: necessary for optimum performance;
- Discrete and time-dependent (function) settings;



Hardware is driven by single corner jaws which determine operational gaps;

Collimation Interlocking

- Inner and outer **thresholds** as a function of time:
 - Applied to each collimator motor axis (4) and gap (2);
 - Encompass the operational tolerance (warnings) and the dump tolerance on the inside and on the outside;
 - → Total of **24 functions** per collimator;
- **Redundancy interlocking (on gaps only):**
 - Max allowed gap vs E_b (2 per collimator);
 - Max and min allowed gap vs β^* (4 per collimator);
- **Temperature interlocks:**
 - 4+1 independent inputs per collimator;










Interlocks on: single corner jaws (driver of hardware) and gaps (actual operational settings);
... + independent temperature checks;

Outline

- Introduction
- **Settings generation, testing and verification**
- Collimator alignment
- XRPs
- Temperature interlocks
- Wish list of changes
- Conclusions

Generation of Collimator Settings

- Jaw corner positions and gaps (mm) are generated based on:
 - Local beam-based parameters (i.e. collimator centres and beam σ) \rightarrow alignment campaigns;
 - Normalised half-gaps ($n\sigma$ settings) \rightarrow aperture measurements and MADX (optics) / SixTrack (cleaning performance) simulations;
 - LVDT offsets;
- Input info is collected at static points (e.g. inj., FT, EoSqueeze, coll.);
 - Time functions are generated offline, saved in .csv files that are then imported into LSA via TRIM editor / LSA app suite;





Beam Mode	Beam Process	
Injection	Ramp@start	 Alignment (All colls)
Ramp	Ramp function	 $f(y, t)$
Flat Top	Ramp@end / Squeeze@start	 Alignment (All except inj. prot.)
Squeeze	Squeeze function	 $f(\beta^*, t)$
Adjust	Squeeze@end / Collisions@start	 Alignment (TCTs)
Adjust	Collisions function	 $f(X_{\text{Inj/Sep}}, t)$
Stable Beams	Collisions@end	 Alignment (TCTs + TCLs)
Levelling	Multi-instances of collisions	

Collimator settings generation is a complex concatenation of measured data and expectations from simulation;

Example: TCT Centre Function

- Functions at TCTs must accommodate all the changes in crossing conditions at the collision IPs, e.g. β^* and shape of collision bumps;
- Jaw corner positions (mm):

$$Pos_{jaw} = C_{coll} \pm n_{(E_b|\beta^*)} \times \sigma_{(E_b|\beta^*)}$$
- Generation:
 - Evolution with time of closed orbit at TCTs as from MADX simulations;
 - Centre from (BPM-based) alignment at extremes of time functions (static points);
 - A good recipe used throughout Run 2 and MDs requiring specific TCT setup!
- Verification by comparing coded functions against BPM readouts during commissioning fills



2018 R&S functions (IR8), fills from initial commissioning with beam with nominal bunches [6544:6569]

Function generation at the best of the present knowledge



07.05 May 2019

Settings Generation, Testing and Verification

- Settings **automatically** generated with dedicated **software**:
 - Flexible and **reproducible** way to generate complex functions;
 - Energy and β^* limits generated in **LSA**, based on the input functions;
 - Software uses **standardized** I/O files, e.g. .csv, .fs, set-up sheet;
 - Alignment results **automatically** stored in **standardized** set-up sheet;
 - Mathematica / Python / LSA;
- **Settings imported in LSA via .csv files**:
 - Minimizes human intervention;
- **Testing and Verification**:
 - *Without beam*: **manual verification** of generated settings by experts:
 - Within functions: graphical cross-checks;
 - Between functions: LSA compare settings;
 - Automated setting checker by G. Valentino;
 - *With beam*:
 - Low-intensity fills to **validate sequencer operation** or looking at various **setting displays** in shade of fills for LMs or other commissioning activities;
 - Machine configurations verified with **LMs**, with cross-checks against similar configurations or simulations;

Generation of settings done such that human errors are at minimum;

Testing and verification of settings done in multiple ways





Outline

- Introduction
- Settings generation, testing and verification
- **Collimator alignment**
- XRPs
- Temperature interlocks
- Wish list of changes
- Conclusions

Collimator Alignment



- Recap of BLM-based alignment:
 - A collimator is **aligned** when both **jaws touch the beam envelop**;
 - Allows to **centre** the collimator around the beam;
 - Reference collimator: possibility to **estimate the local beam size**;
- Starting from 2011: **semi-automatic** collimator alignment:
 - The collimator moves until the **BLM signal exceeds a threshold**;
- Roles of **collimation expert** during alignment:
 - Set **threshold** and recognize **alignment spikes**;
 - Cycle** alignment procedure on the desired collimators and **acknowledge** results of alignment;



Alignment procedure long and requiring 4/5 collimation experts in the CCC

Fully Automatic Collimator Alignment

- Fully automatic BLM-based alignment:
 - A **controller FESA class** cycles the alignment among collimators;
 - BLM spike recognition done via **Machine Learning (ML)**:
 - 6 ML models trained independently are used;
 - The majority vote among all models is used;
 - 95% of precision;
 - Single jaw alignment **repeated twice**:
 - 1st one: to get both jaws actually touching the beam;
 - 2nd one: to make sure jaw is at contact with beam;
 - **Automatic BLM threshold selection** (for stopping moving jaw):
 - max: 2E-04;
 - Start with latest BLM signals at collimators and then increased in steps until jaw can move;
 - Automatic saving of settings;
 - Suitable also for **angular** alignment!




Automatic collimator alignment faster than the semi-automatic
+ requiring only a collimation experts in the CCC

Courtesy of G. Azzopardi

Collimator Alignment: 2018

- 2018 Collimator alignment campaign carried out only with fully automatic collimator alignment;
 - Centres deployed for operation!
- Very good reproducibility wrt 2017 alignment results, especially in IR3 & IR7, where no changes in optics occurred;

Fully automatic alignment is reliable.



Courtesy of G. Azzopardi



Outline

- Introduction
- Settings generation, testing and verification
- Collimator alignment
- **XRP**s
- Temperature interlocks
- Wish list of changes
- Conclusions



TOTEM & PPS XRPs before LS2



Run 1:

- XRPs (almost) exclusively used in low-lumi special runs (as designed)
- End of run 1: extension of physics programme to include operation in standard runs
 - first insertion tests in 2012 revealed serious impedance problems (temperature, vacuum)

LS1:

Upgrade of the XRP system:

- Total number of jaws: 12 → 26, addition of new cylindrical pots (impedance-friendly design)
- Impedance mitigation:
 - exchange of ferrites, new ferrites with better geometry, RF shields to avoid cavities

Run 2:

- Successful intensity ramp-up to the highest LHC luminosities without problems (monitoring of BLM rates, temperatures, vacuum, beam stability)
- Insertion in almost all standard fills
- Initial stability problems in PXI software, solved within first year of Run 2, then very stable.
- Very rare problems with LVDT readout amplifiers ($O(1$ per year))
 - spiky signal exceeds warning limit → XRP extraction with springs, in 1 case (2017): spurious dump
 - implementation of filter in LVDT FPGA code (interlock after 3 readings = 30 ms over limit), internal post-mortem file generated if any limit is crossed even once.
- Occasional ($O(1$ per year)) connectivity problems with microswitches (broken solderings)
 - OUT-stopper and IN-stopper position signals wrong
 - no danger, but can block operation.




TOTEM & PPS: LS2 Interventions



LS2:

- vertical beamline levelling in LSS5 by -3 mm including Roman Pots
 - New detector packages for all tracking and timing Roman Pots
 - Move RF shield from unused unit XRPH.C6 to empty unit XRPH.A6 , C6 removed (replaced with beampipe), A6 to be equipped with diamond timing detectors
- Full metrological survey of all Roman Pots needed



- Movement system change as proposed by EN-SMM (and discussed in TREX, 12.12.2018)
 - communication between CCC and PXI directly with CMW, no DIM anymore
 - simplified internal communication between the two PXIs

Commissioning after LS2:

- Movement and **full** interlock tests (incl. beam-mode dependent tests)
- Beam-based alignment

Outline


- Introduction
- Settings generation, testing and verification
- Collimator alignment
- XRPs
- **Temperature interlocks**
- **Wish list of changes**
- Conclusions

Temperature Interlocks

- **Jaw temperatures** reflect the **load** on collimators due to **slowly varying** drops of beam lifetime;
- Temperature of jaws (4) and cooling water (1) are monitored and interlocked;
- 2 sensors per jaw:
 - Warning: >45°C;
 - Dump: >50°C;
- 1 sensor on the outgoing cooling channel
 - Warning: >30°C;
 - Dump: >35°C;



10 blocked during RUN1 and 34 blocked during RUN2. + 20 blocked on the TDI. During LS2 "intelligent" algorithm will mitigate this effect recognizing broken temperature in real-time avoiding unwanted beam dumps

Failures during RUN2



Courtesy of M. Di Castro

- In Run 1 and Run 2, **issues with faulty temperature readings** led to disabling the sensors;
- Only **1 dump** in Run 2!
- Upgrade to **intelligent algorithm** for faulty sensors on-going;



Wish List of Changes

- We have enough maturity in **generating collimator settings** outside LSA to try the implementation in LSA;
 - do not depend on specific experts (e.g. R. Bruce for $n\sigma$ function, A. Mereghetti for TCT centre functions);
- Full deployment of ML and **fully automatic alignment** in Run 3;
- Ramp functions to **crystal** control system;
- Proposed changes in automatic disabling **temperature sensors** with erratic readouts;
- First **online LM analysis** in CCC before final validation (see D. Mirarchi's presentation) + possibility to collect reference LMs per machine and beam mode;
- Considering improvements in **settings checker**;

A large set of improvements;
Their achievement heavily depends on actual man-power available!

Outline

- Introduction
- Settings generation, testing and verification
- Collimator alignment
- XRPs
- Temperature interlocks
- Wish list of changes
- **Conclusions**

Conclusions

- The LHC **collimation system** is at the forefront of LHC protection during every phase with beams;
 - **Reliability** and **safety** are essential ingredients for the excellent performance achieved so far;
 - System with unprecedented complexity and amount of degrees of freedom;
- **Settings** generation and **interlocking** are activities essential to grant reliability and safety;
 - The collimator settings and interlocks were recalled;
 - Their generation and verification cycle was presented;
- **2018 alignment campaigns** carried out with **fully automatic alignment**;
 - Results safely deployed in 2018 in operation;
 - Comparison with human BLM-based alignment shows full **reliability** of results;
- **Temperature interlocks** worked fine in Run 2;
 - On-going development to **automatic identification** and **disabling** of faulty sensors;
- **XRPs** will undergo an important upgrade in the movement control system;
 - As discussed in TREX meeting (12 Dec 2018);
 - Full survey of XRPs + movement and interlock tests in initial commissioning with beam;
- A wish list of **software changes** has been drafted;
 - Actual **achievements** will depend on available **man-power**;



Thanks for your attention!
...questions?

