



Contribution ID: 66

Type: **contributed talk**

## The ATLAS ITk Strip Detector Sensors for the Phase-II LHC Upgrade

*Monday, 17 February 2020 14:55 (20 minutes)*

The ATLAS experiment at the Large Hadron Collider is currently preparing for a major upgrade of the Inner Tracking for the Phase-II LHC operation (known as HL-LHC), scheduled to start in 2026. In order to achieve the integrated luminosity of 4000 fb<sup>-1</sup>, the instantaneous luminosity is expected to reach unprecedented values, resulting in about 200 proton-proton interactions in a typical bunch crossing. The radiation damage at the full integrated luminosity implies integrated hadron fluencies over  $2 \times 10^{16}$  neq/cm<sup>2</sup> requiring a complete replacement of the existing Inner Detector. An all-silicon Inner Tracker (ITk) is under development with a pixel detector surrounded by a strip detector, aiming to provide increased tracking coverage up to  $|\eta|=4$ .

The ITk Strip Detector system consisting of four barrel layers in the centre and forward regions composed of six disks at each end, is described in the ATLAS Inner Tracker Strip Detector Technical Design Report (TDR). With the recent completion of Final Design Reviews (FDRs) in a number of key areas, such as Sensors, modules, ASICs and front-end electronics, the prototyping phase has been completed successfully. The pre-production phase is about to start at the institutes involved.

In this contribution we present a detailed overview of the ITk Strip Detector Sensors, highlight the final design choices and give an extended summary of the R&D results achieved in the prototyping phase.

**Presenter:** HOMMELS, Bart (University of Cambridge (GB))

**Session Classification:** HEP Systems

**Track Classification:** Planar sensors