



Status of the LHC Injectors Upgrade (LIU) project

in 4th ICFA Mini-Workshop on Space Charge 2019, 4-6 November, CERN, Geneva

Hannes Bartosik, Malika Meddahi, Giovanni Rumolo

R. Alemany, G. Bellodi, J. Coupard, H. Damerau, G.P. Di Giovanni, A. Funken,
B. Goddard, K. Hanke, A. Huschauer, V. Kain, A. Lombardi, B. Mikulec,
F. Pedrosa, S. Prodon, R. Scrivens, E. Shaposhnikova

<https://indico.cern.ch/event/828559/>

Outline



- LHC beam performance of the injectors complex and upgrade
- LIU project timelines
- Relevance of space charge within LIU
- Conclusions

Outline




- LHC beam performance of the injectors complex and upgrade
 - Pre-LIU performance
 - Definition of the LIU goals and baseline upgrades
- LIU project timelines
- Relevance of space charge within LIU
- Conclusions




The CERN injector complex: protons

Large Hadron Collider (LHC)
 $C = 27 \text{ km}$
 $E_{kin}^{out} = 6.5 \text{ TeV}$



PS-Booster (PSB)
4 rings of $C = 157 \text{ m}$
 $E_{kin}^{out} = 1.4 \text{ GeV}$




The **CERN injector complex** is used to feed **LHC** as well as to serve a number of fixed target experiments






Production scheme of LHC beams

Large Hadron Collider (LHC)
C = 27 km
 $E_{kin}^{out} = 6.5$ TeV



PS-Booster (PSB)
4 rings of C = 157 m
 $E_{kin}^{out} = 1.4$ GeV



Proton Synchrotron (PS)
C = 628 m
 $E_{kin}^{out} = 25$ GeV

Linac 2
 $E_{kin}^{out} = 50$ MeV


Beam transfer	Number of bunches	Bunch spacing (ns)
Linac2 → PSB $E_{kin}^{out} = 50$ MeV	Multi-turn injection of coasting beam	—






Production scheme of LHC beams

Large Hadron Collider (LHC)
C = 27 km
 $E_{kin}^{out} = 6.5 \text{ TeV}$



PS-Booster (PSB)
4 rings of C = 157 m
 $E_{kin}^{out} = 1.4 \text{ GeV}$

Proton Synchrotron (PS)
C = 628 m
 $E_{kin}^{out} = 25 \text{ GeV}$



Linac 2
 $E_{kin}^{out} = 50 \text{ MeV}$


Beam transfer	Number of bunches	Bunch spacing (ns)
Linac2 → PSB $E_{kin}^{out} = 50 \text{ MeV}$	Multi-turn injection of coasting beam	—
PSB → PS $E_{kin}^{out} = 1.4 \text{ GeV}$	4 + 2	272






Production scheme of LHC beams

Large Hadron Collider (LHC)
C = 27 km
 $E_{kin}^{out} = 6.5$ TeV



PS-Booster (PSB)
4 rings of C = 157 m
 $E_{kin}^{out} = 1.4$ GeV



Linac 2
 $E_{kin}^{out} = 50$ MeV

Beam transfer	Number of bunches	Bunch spacing (ns)
Linac2 → PSB $E_{kin}^{out} = 50$ MeV	Multi-turn injection of coasting beam	—
PSB → PS $E_{kin}^{out} = 1.4$ GeV	4 + 2	272


One triple bunch splitting and two double bunch splittings in the PS






Production scheme of LHC beams

Large Hadron Collider (LHC)
C = 27 km
 $E_{kin}^{out} = 6.5 \text{ TeV}$



PS-Booster (PSB)
4 rings of C = 157 m
 $E_{kin}^{out} = 1.4 \text{ GeV}$



Linac 2
 $E_{kin}^{out} = 50 \text{ MeV}$


Beam transfer	Number of bunches	Bunch spacing (ns)
Linac2 → PSB $E_{kin}^{out} = 50 \text{ MeV}$	Multi-turn injection of coasting beam	—
PSB → PS $E_{kin}^{out} = 1.4 \text{ GeV}$	4 + 2	272
PS → SPS $E_{kin}^{out} = 25 \text{ GeV}$	72	25

Four injections into the SPS



LHC beam performance before upgrade

- LHC beam parameters at the **SPS extraction (450 GeV)** result from **intensity** and **brightness** limitations of all injectors in the chain



- **Brightness**

- PSB brightness determined by space charge at injection
- Limit for PS space charge at injection $\Delta Q_y < 0.31$


- **Intensity**

- SPS is limited by beam loading and longitudinal instabilities on the ramp and flat top
- PS is limited by longitudinal coupled bunch instability on the ramp and flat top

LHC beam performance before upgrade



- LHC beam parameters at the **SPS extraction (450 GeV)** result from **intensity** and **brightness** limitations of all injectors in the chain



- **Brightness**

- PSB brightness determined by space charge at injection
- Limit for PS space charge at injection $\Delta Q_y < 0.31$
- ✓ *Space charge in SPS not a limit for LHC beams*


- **Intensity**

- SPS is limited by beam loading and longitudinal instabilities on the ramp and flat top
- PS is limited by longitudinal coupled bunch instability on the ramp and flat top
- ✓ *PSB intensity limit well above displayed range*



The LHC Injectors Upgrade (LIU) project

- **Performance goal** → Match the beam parameters at **SPS extraction** to the **High Luminosity LHC (HL-LHC) target**



	N_b ($\times 10^{11}$ p/b)	$\epsilon_{x,y}$ (μm)
HL-LHC target	2.3	2.1
Before upgrades	1.3	2.7


- **LIU strategy**

- Identify the sources of the performance limitations in each of the injectors impeding the achievement of the HL-LHC target parameters
- Define and deploy the necessary upgrade items to overcome these limitations

The LHC Injectors Upgrade (LIU) project




- Effect on **beam parameter reach at SPS extraction** of the upgrade items in the LIU project baseline




The LHC Injectors Upgrade (LIU) project



- Effect on **beam parameter reach at SPS extraction** of the upgrade items in the LIU project baseline



- **Connection of PSB to Linac4**
 - Charge exchange H^- injection at 160 MeV into PSB




The LHC Injectors Upgrade (LIU) project



LHC Injectors Upgrade

- Effect on **beam parameter reach at SPS extraction** of the upgrade items in the LIU project baseline



✓ Connection of PSB to Linac4

- **PSB acceleration to 2 GeV**

- Reduced $\beta\gamma^2$ at PS injection by 40%
- Updated longitudinal parameters at PSB-PS transfer to further reduce PS space charge tune spread




The LHC Injectors Upgrade (LIU) project



LHC Injectors Upgrade

- Effect on **beam parameter reach at SPS extraction** of the upgrade items in the LIU project baseline



- ✓ Connection of PSB to Linac4
- ✓ PSB acceleration to 2 GeV
- **PS RF upgrades, e.g.**
 - New Finemet cavity for longitudinal feedback system
 - Impedance reduction of RF systems



The LHC Injectors Upgrade (LIU) project



LHC Injectors Upgrade


- Effect on **beam parameter reach at SPS extraction** of the upgrade items in the LIU project baseline



- ✓ Connection of PSB to Linac4
- ✓ PSB acceleration to 2 GeV
- ✓ PS RF upgrades

- **SPS upgrade**

- Power and LLRF upgrade of 200 MHz RF system
- Longitudinal impedance reduction
- a-C coating of focusing quadrupole chambers
- Deployment of low γ_t optics
- Upgrade of beam dump and protection devices




The LHC Injectors Upgrade (LIU) project



LHC Injectors Upgrade

- Effect on **beam parameter reach at SPS extraction** of the upgrade items in the LIU project baseline



✓ Connection of PSB to Linac4

✓ PSB acceleration to 2 GeV

✓ PS RF upgrades


- **SPS upgrade**

- Power and LLRF upgrade of 200 MHz RF system
- Longitudinal impedance reduction
- a-C coating of focusing quadrupole chambers
- Deployment of low γ_t optics
- Upgrade of beam dump and protection devices



The LHC Injectors Upgrade (LIU) project

- Effect on **beam parameter reach at SPS extraction** of the upgrade items in the LIU project baseline



- ✓ Connection of PSB to Linac4
- ✓ PSB acceleration to 2 GeV
- ✓ PS RF upgrades
- ✓ SPS upgrade


⇒ **LIU parameter reach for proton beams matches the HL-LHC target within baseline**

Not only protons ...






- CERN injector complex also accelerates **heavy ions (Pb)**

Large Hadron Collider (LHC)
 $C = 27 \text{ km}$
 $E_{kin}^{out} = 2.6 \text{ TeV/u}$



	N (x 10 ⁸ ions/b)	ϵ (μm)	# of bunches
HL-LHC target (7x 8 bunches, 50 ns)	1.9	1.5	1248



Single bunch parameters
already achieved


Relies on SPS
slip stacking



Outline



- LHC beam performance of the injectors complex
- **LIU project timelines**
 - Project evolution
 - Current status and future steps
- Relevance of space charge within LIU
- Conclusions



Run 1 + LS1 + Run 2 (2010 – 2018)
Preparing, defining, testing, executing

- **Start of LIU project**
- Studies, advanced installation and testing, new buildings
- **Linac4** commissioning and quality/reliability runs

Long Shutdown 2 (2018 – 2020)
Peak of LIU execution phase


- End of LIU equipment production
- **LIU equipment installation** across all injectors

Run 3 (2020 – 2024)

- **Recommissioning** of upgraded injectors
- **End of LIU project in 2021!**

→ Beam commissioning to **LIU specifications** throughout Run 3





Run 1 + LS1 + Run 2 (2010 – 2018)
Preparing, defining, testing, executing

- Start of LIU project
- Studies, advanced installation and testing, new buildings
- Linac4 commissioning and quality/reliability runs

Long Shutdown 2 (2018 – 2020)
Peak of LIU execution phase

- End of LIU equipment production
- LIU equipment installation across all injectors

Run 3 (2020 – 2024)

- Recommissioning of upgraded injectors
- **End of LIU project in 2021!**

→ Beam commissioning to LIU specifications throughout Run 3



Time lapse




Emptying part of PSB injection area, before installing the new H⁻ charge exchange injection system



Hardware and beam commissioning in 2020



J. Coupard *et al.*, LS2 Master Schedule v.2.3 (Released) – [EDMS 1687788](#)




- Hardware commissioning/cold check out
- Beam commissioning



LIU beam ramp up

LIU beam commissioning plan: a gradual intensity ramp up all through Run 3






Outline



- LHC beam performance of the injectors complex and upgrade
- LIU project timelines
- **Relevance of space charge within LIU**
 - Tune spreads across the injectors chain for proton
 - Ions in LEIR and SPS
- Conclusions



Tune spread across proton injectors (pre-LIU)

- Space charge plays a crucial role for brightness across the injector chain
 - Large tune spread at PSB injection already mitigated with
 - Injection on the ramp with capture in h=2 BSM
 - Dynamic working point and resonance compensation





Tune spread across proton injectors (pre-LIU)

- Space charge plays a crucial role for brightness across the LHC injector chain
 - Large tune spread at PS injection
 - Crammed between integer resonance and space charge driven structural resonance
 $8Q_y=50$ during **1.2 sec flat bottom**




Tune spread across proton injectors (pre-LIU)

- Space charge plays a crucial role for brightness across the LHC injector chain
 - Tune spread in SPS still has margin
 - However, long flat bottom – other effects? E.g. effect of space charge on instability thresholds, interplay with e-cloud, ...



Tune spread across proton injectors (post-LIU)

- Space charge plays a crucial role for brightness across the LHC injector chain
 - After LIU, the tune spreads will stay approximately the same up to PS injection
 - Increase of PSB and PS injection energy + larger longitudinal emittance at PSB-PS transfer allow for double intensity within the same transverse emittance and same tune spread
 - SPS tune spread gets closer to its limit of 0.21



Tune spread across proton injectors (post-LIU)



LHC Injectors Upgrade

- Space charge plays a crucial role for brightness across the LHC injector chain
 - After LIU, the tune spreads will stay approximately the same up to PS injection
 - Increase of PSB and PS injection energy + larger longitudinal emittance at PSB-PS transfer allow for double intensity within the same transverse emittance and same tune spread
 - SPS tune spread gets closer to its limit of 0.21
- ⇒ **Still to demonstrate** with continuing simulations and then with beam
- New PSB brightness line with new injection scheme and new magnetic errors from BSW
 - Validity of PS tune spread limit at 2 GeV and with new injection elements
 - Benefits from larger longitudinal emittance at PS injection
 - No detrimental effects from larger SPS tune spread (and compatibility with the possible request of lower longitudinal emittance from PS)
 - Capability of staying within the tight emittance growth budgets in all machines
 - ...


**A dense and challenging program in front of us
→ Necessary for efficient beam
commissioning in Run 3**



Space charge for the ions: LEIR





- Intensive study program + hardware upgrades during Run 2 led to impressive **performance boost**
 - **Mitigation of space charge** and IBS at RF capture was a breakthrough in 2015, mainly through working point optimization and bunch flattening
 - Process optimised over the years contributing to further improved LEIR performance in 2016-2018
 - More work ongoing on active resonance compensation and electron cooling optimization **to further reduce brightness effects at RF capture**



Space charge for the ions: SPS

- Space charge effects on Pb ion beams in the SPS are not negligible
 - Large space charge tune spreads ($|\Delta Q_y| > 0.21$) along long flat bottom (14 injections)
 - Intensity dependent transmission
 - Losses, emittance growth, bunch shortening
 - Simulations ongoing to pin down mechanism





Conclusions

- **LIU project baseline** fulfils the HL-LHC target parameters
 - LS2 works now ongoing in all the injectors to put in place the upgrades
- **LIU hardware and beam commissioning** will start in 2020
 - HL-LHC ion beams to be commissioned by the end of 2021
 - Performance ramp up defined for LIU proton beams throughout Run 3
- **Space charge** a fundamental ingredient to define LIU baseline
 - Steered the choices for injection energy into PSB and PS
 - Important limitation crucial to improve ion beams in LEIR and SPS
 - Simulations still ongoing for all machines to improve predictions, define and guide operational scenarios for post-LIU performance



Conclusions

- **LIU project baseline** fulfils the HL-LHC target parameters
 - LS2 works now ongoing in all the injectors to put in place the upgrades
- **LIU hardware and beam commissioning will start in 2020**
 - HL-LHC ion beams to be commissioned by the end of 2020
 - Performance ramp up defined for LIU proton beams
- **Space charge** a fundamental ingredient to:
 - Steered the choices for injection energy into PSB and PS
 - Important limitation crucial to improve ion beams in LEIR and SP
 - Simulations still ongoing for all machines to improve predictions, define a set of operational scenarios for post-LIU performance

LHC injectors will be operating in uncharted territory after LS2
The production of brighter beams and the brightness preservation along the injector chain will be a big challenge and instrumental for the success of LIU!




www.cern.ch




*THANK YOU
FOR YOUR
ATTENTION*

A quick overview on the LIU project


- **2 GeV** injection → Reduced space charge at PS injection
- New **RF** equipment including broad-band feedback → Increased instability threshold



- Acceleration of H^- to **160 MeV**
- Target 25 mA within $0.3 \mu m$



- Main **RF** system (200 MHz) upgrade → Increased RF power and improved controls
- Longitudinal **impedance** reduction & partial a-C coating → Increased instability thresholds
- New **beam dump** and protection devices




- **160 MeV** H^- charge exchange injection → Reduced space charge at PSB injection
- Acceleration to **2 GeV** with new main power supply and new RF systems






A quick overview on the LIU project

Large Hadron Collider (LHC)
 $C = 27 \text{ km}$
 $E_{kin}^{out} = 6.5 \text{ TeV}$







- For all injectors :**
- Replacement of ageing/sensitive hardware
 - New/upgraded beam instrumentation and diagnostics devices, vacuum systems, software tools, machine protection, electrical services, cooling and ventilation
 - ...





The CERN injector complex: Pb ions

Large Hadron Collider (LHC)
C = 27 km
 $E_{kin}^{out} = 2.6 \text{ TeV/u}$






Beam transfer	Number of bunches	Bunch spacing (ns)
Linac3 → LEIR $E_{kin}^{out} = 4.2 \text{ MeV/u}$	Multi-turn injection of coasting beam	—
LEIR → PS $E_{kin}^{out} = 72.2 \text{ MeV/u}$	2 (3)	354 (472)
PS → SPS $E_{kin}^{out} = 5.9 \text{ GeV/u}$	4 (3)	100 (75)
SPS → LHC $E_{kin}^{out} = 176.4 \text{ GeV}$	14 x 4 (14 x 3)	100 / 150 (75 / 150)



Hihglights (2): Electron cloud in SPS


- **Electron cloud mitigation in SPS** will mainly rely on
 - Beam induced scrubbing
- Industrialisation of **in-situ a-C coating** of magnet chambers developed and demonstrated for potential **application after LS2**



Achievements (4): Wideband Feedback System



- Prototype of vertical (V) WBFS deployed at SPS
 - Using stripline pick-ups + two stripline kickers and a slotline kicker, bandwidth up to 1 GHz, power > 1 kW
- Damping of Transverse Mode Coupling Instability (TMCI) with single bunch demonstrated in machine experiments in 2017-18



Achievements (4): Wideband Feedback System

- Prototype of vertical (V) WBFS deployed at SPS
 - Using stripline pick-ups + two stripline kickers and a slotline kicker, bandwidth up to 1 GHz, power > 1 kW
- Damping of Transverse Mode Coupling Instability (TMCI) with single bunch demonstrated in machine experiments in 2017-18
- Operational deployment not pursued within LIU, however kept as **post-LS2 option** in case of unexpected transverse instabilities to reach LIU parameters






LIU beam ramp-up – possible additional needs

To follow-up and document post-LS2 upgrades list at the defined checkpoints

Item	Decision point	Cost estimate (MCHF)
Booster extraction kicker impedance reduction	2021	0.1
Landau cavity	2023	4
a-C coating of all MBBs, quads + 159 drifts	2023 – 2024	4
Further impedance reduction (SPS injection kicker, flanges & valves shielding)	2022 – 2023	0.2 + 3.5
Remaining QD aperture improvement	2021	0.6
New wideband feedback system	2022 – 2023	>2
Final BSRT	2022	0.2
New collimation system	2022 – 2023	1



Lifting the PS intensity limitation



- Bunch current limited to **1.6e11 p/b at extraction**
- Above 1.6e11 p/b **longitudinal coupled bunch instabilities** appear on the ramp and at flat top for nominal longitudinal emittance
 - Dipolar oscillation, caused by **10 MHz RF system impedance** (as found also in simulations)

Lifting the PS intensity limitation

- **Longitudinal feedback** based on broad-band Finemet cavity as kicker installed and deployed over the last three years → stabilizes above $2e11$ p/b






Lifting the PS intensity limitation

- **Longitudinal feedback** based on broad-band Finemet cavity as kicker installed and deployed over the last three years → stabilizes above $2e11$ p/b
- **Impedance reduction** of the 10 MHz cavities with upgrade of power amplifier → currently tested on one cavity, to be deployed on all cavities in LS2
- Ongoing study on the option of a **higher harmonic ('Landau') cavity** to have another weapon against longitudinal instabilities and reach the target LIU/HL-LHC intensity




Lifting the SPS intensity limitation

- **Beam loading** in the present 200 MHz TW RF system – intensity limited to about $1.3e11$ p/b
- **Longitudinal instabilities** during ramp with very low threshold currently cured by
 - 800 MHz RF system in bunch shortening mode
 - Controlled emittance blow-up (with constraint of 1.7 ns bunch length at extraction)



Lifting the SPS intensity limitation

- **Impedance reduction** needed in addition
 - Shielding of a subset of vacuum flanges
 - Enhanced damping of HOMs of 200 MHz (factor 2) (baseline for LIU)
 - Serigraphy on the kickers MKP



Other SPS intensity limitations?

- **Transverse Mode Coupling Instability (TMCI)** threshold was raised from 1.6×10^{11} p/b to 4×10^{11} p/b when switching to a low gamma transition (γ_t) optics

