



CF

Computing Facilities

CERN IT
Department

Quattor@CERN


Quattor Workshop March 2010

Véronique Lefébure


CERN-IT-CF-ASI

- CDB v2.2.5 & PANC 8.2.11
 - .htaccess file now accepted under /var/lib/cdb/hld/checkout
 - ~10000 profiles
- PANC 8.3.0 tested
 - CDB updated for the new .dep format, changes not committed to SVN yet.
 - V 8.3.1. not tested yet

Successful commits / hour (last month)
~ up to 260 commits per day




Changed templates / hour (last month)



Click on edges to resize the chart

Changed profiles / hour (last month)



Search CDB

Django-based Search tool for CDBSQL
By David Rodrigues (SQLAlchemy)

Choose search field

Choose search field

Choose search field

Choose search field

Choose search field

Additional path

Display information Default Custom

Accounting Name Architecture Cluster Name Cluster Subname

Cluster Type Contract ID Contract Type Domain

Gateway Hardware Model Hardware Type Hostname

IP Address Importance Kernel Version Location Room

Netmask Network Domain Network Hostname No Contact Timeout

Operating System Ping Timeout Quattor Managed Rack

SURE Status Serial number Service Manager Stage

State System Function User Contact Vendor

Quattor All Quattor Managed Non-Quattor Managed

Ordered by

Output

HTML, Excel or XML output

NOTE: The OR operator has greater precedence than the AND operator, meaning that all OR operations will be inside brackets.

- Work by Daniel Lenkes, with the help of Luis Mejas.
- ~<3 days.
- Test with one profile and CERN template tree structure
- Observations
 - We had to move the profiles from /profiles/ to /cluster/xxx/profiles: is it mandatory or can that be configured ?
 - Svn commit and deploy should be an atomic transaction
 - What happens if the deploy process fails?
 - Svn acls at the level of directories and not files is a disadvantage
 - Stages prod/preprod/test heavy: need to copy the full cluster tree, cluster per cluster. How do you handle 100 clusters ?
 - Advantages:
 - Build-in acl's
 - Local panc compilation allows access to log files and debugging tools

- Pkg_add, pkg_repl (<https://savannah.cern.ch/bugs/?64229>)
 - Suggest to discourage the use of explicit versions, by
 - adding "reason" and "date" parameters to pkg_add/pkg_repl for those cases where the version is given (and make these two mandatory) - these need to be used to document `_why_` a default version isn't being used. Ideally insist on a recognizable Bug#id/Ticket to ensure that the item is really tracked somewhere..
 - making pkg_add/pkg_repl give a WARN in case an explicit version is being used (perhaps exempt some templates (such as `.../component/NAME/config`), so that a "designated maintainer" can override a default).

- Can we agree on a policy for change announcements (new version of components etc)?
- Seems that there is more traffic on quattor-grid than on quattor-discuss: do we really need 2 mailing lists ?
- At CERN: we will setup a Forum for user support