CALOR 2022 - 19th International Conference on Calorimetry in Particle Physics



Contribution ID: 113

Type: not specified

The SiD Digital ECal Based on Monolithic Active Pixel Sensors

The SiD Collaboration has had a long interest in the potential for improved granularity in the tracker and ECal; a study of MAPS in the SiD ECal was described in the ILC TDR. Work is progressing on the MAPS application in an upgraded SiD design, both for the ECal and tracking. A prototyping design effort is underway for a common SiD tracker/ECal design based on stitched reticules to achieve 10 x 10 cm² sensors with 25 x 100 micron² pixels. Application of large area MAPS in these systems would eliminate delicate and expensive bump-bonding, provide possibilities for better timing, and should be significantly cheaper due to being a more conventional CMOS foundry process. The small pixels significantly improve shower separation. Recent simulation studies confirm previous results, indicating electromagnetic energy resolution based on digital hit cluster counting provides better performance than the SiD TDR analog design based on 13 mm² pixels. Furthermore, the two shower separation is excellent down to the millimeter scale. Geant4 simulation results will be presented demonstrating these expectations.

Authors: VERNIERI, Caterina (SLAC National Accelerator Laboratory (US)); BRAU, Jim (University of Oregon (US)); ROTA, Lorenzo (SLAC); BREIDENBACH, Martin (SLAC)