

Latest Results on the Radiation Tolerance of Diamond Pixel and Pad Detectors

Wednesday, July 29, 2020 3:45 PM (15 minutes)

As nuclear and high energy facilities around the world are upgraded and move to higher and higher intensities, the detectors in use at these facilities must become more radiation tolerant. Diamond is a material in use at many facilities due to its inherent radiation tolerance and ease of use. We present the results of recent radiation tolerance measurements of the highest quality poly-crystalline Chemical Vapor Deposition (pCVD) diamond material for a range of proton energies, pions and neutrons up to a fluence of 2×10^{16} particles/cm². From this data we derive the damage constants as a function of energy and particle species. We also present the recent measurements of the rate dependence of pulse height for non-irradiated and irradiated pCVD diamond pad and pixel detectors. The results we present include detectors tested over a range of particle fluxes up to 20 MHz/cm² with both pad and pixel readout electronics. Our results indicate the pulse height of unirradiated poly-crystalline CVD diamond detectors and the neutron irradiated poly-crystalline CVD diamond detectors measured with the pad readout show no dependence on the particle flux.

Secondary track (number)

12

Primary authors: KAGAN, Harris (Ohio State University (US)); TRISCHUK, William (University of Toronto (CA)); ON BEHALF OF THE RD42 COLLABORATION

Presenter: TRISCHUK, William (University of Toronto (CA))

Session Classification: Detectors for Future Facilities (incl. HL-LHC), R&D, Novel Techniques

Track Classification: 13. Detectors for Future Facilities (incl. HL-LHC), R&D, Novel Techniques