

Development of a System for Abort and Luminosity of the ATLAS Experiment at the HL-LHC based on polycrystalline CVD diamond

Tuesday 28 July 2020 17:30 (15 minutes)

The High Luminosity upgrade of Large Hadron Collider (HL-LHC) will increase LHC Luminosity by an order of magnitude increasing the density of particles on the detector by an order of magnitude. For protecting the inner detectors of experiments and for monitoring the delivered luminosity, a radiation hard beam monitor is being developed. We are developing a set of detectors based on poly-crystalline Chemical Vapor Deposition (pCVD) diamonds and a dedicated ASIC. Due to the large range of particle flux through the detector, flexibility is very important. To satisfy the constraints imposed by the HL-LHC, our solution is based on segmenting each single diamond sensor into multiple devices of varying size and reading them out with a new multichannel readout chip. In this talk we describe the proposed system, present preliminary results from the first detectors fabricated using our prototype ASIC and present the noise distribution and efficiency for single MIPs.

I read the instructions

Secondary track (number)

13

Primary authors: GORISEK, Andrej (Jozef Stefan Institute (SI)); KAGAN, Harris (Ohio State University (US)); Prof. MIKUZ, Marko (Jozef Stefan Institute (SI)); MACEK, Bostjan (Jozef Stefan Institute (SI)); SMITH, Dale Shane (Ohio State University (US)); ABUSAREYA, Moamen (Ohio State University); TRISCHUK, William (University of Toronto (CA))

Presenter: Prof. MIKUZ, Marko (Jozef Stefan Institute (SI))

Session Classification: Detectors for Future Facilities (incl. HL-LHC), R&D, Novel Techniques

Track Classification: 13. Detectors for Future Facilities (incl. HL-LHC), R&D, Novel Techniques