

ATLAS ITk Pixel Detector Overview

Tuesday 28 July 2020 15:45 (15 minutes)

For the HL-LHC upgrade the current ATLAS Inner Detector is replaced by an all-silicon system. The Pixel Detector will consist of 5 barrel layers and a number of rings, resulting in about 14 m² of instrumented area. Due to the huge non-ionizing fluence (1e16 neq/cm²) and ionizing dose (5 MGy), the two innermost layers, instrumented with 3D pixel sensors (L0) and 100µm thin planar sensors (L1) will be replaced after about 5 years of operation. All hybrid detector modules will be read out by novel ASICs, implemented in 65nm CMOS technology, with a bandwidth of up to 5 Gb/s. Data will be transmitted optically to the off-detector readout system. To save material in the servicing cables, serial powering is employed for low voltage. Large scale prototyping programs are being carried out by all sub-systems. The talk will give an overview of the layout and current status of the development of the ITk Pixel Detector.

I read the instructions

Secondary track (number)

Primary author: TERZO, Stefano (IFAE Barcelona (ES))

Presenter: TERZO, Stefano (IFAE Barcelona (ES))

Session Classification: Detectors for Future Facilities (incl. HL-LHC), R&D, Novel Techniques

Track Classification: 13. Detectors for Future Facilities (incl. HL-LHC), R&D, Novel Techniques