## Student workshop on superconductivity and applications



Contribution ID: 30

Type: not specified

## Update on Nb thick films on Cu for 6GHz cavities

Thursday 8 October 2020 16:30 (20 minutes)

One of the well-known difficulties concerning the performances of the Nb coated Cu cavities, is the reproducibility of the results. Two cavities fabricated by the same method and sputtered with the same deposition parameters, may present different performances during the RF characterization. Two main approaches are taken into consideration for this research: substrate and film reproducibility. In order to improve the substrate reproducibility, the standard mechanical grinding of the 6GHz cavities, that leads to defects on the inner surface of the cavities that can remain even after chemical treatments, has been replaced for Vibrotumbling technique in order to improve the inner surface of the cavities. For the film reproducibility, a Nb thick film between 40 and 70 microns is deposited to reproduce the bulk niobium superconducting properties. On the other hand, we report the experimental results concerning a material study (Nb bulk, Nb on Cu thin film and Nb on copper thick film) under the effect of the magnetic flux trapped in 6 GHz cavities.

**Authors:** Mrs GARCIA DIAZ, Vanessa (INFN-LNL, Università degli Studi di Ferrara); CHYHYRYNETS, Eduard (INFN - National Institute for Nuclear Physics); PIRA, Cristian (LNL-INFN); Mr STIVANELLO, Fabrizio (INFN-LNL); Mr MATTEO, Zanierato (Università degli studi di Padova)

Presenter: Mrs GARCIA DIAZ, Vanessa (INFN-LNL, Università degli Studi di Ferrara)

Session Classification: Session 4 - Day 1 - PM