

# 3D non-linear MHD simulations of deuterium shattered pellet injection into H-mode JET plasma

M. Kong<sup>1</sup>, E. Nardon<sup>2</sup>, M. Hoelzl<sup>3</sup>, D. Bonfiglio<sup>4</sup>, D. Hu<sup>5</sup>, A. Boboc<sup>1</sup>, P. Carvalho<sup>1</sup>, T.C. Hender<sup>1</sup>, S. Jachmich<sup>6</sup>, K. D. Lawson<sup>1</sup>, U. Sheikh<sup>7</sup>, S. Silburn<sup>1</sup>, R. Sweeney<sup>8</sup>, G. Szepesi<sup>1</sup>, the JOREK team\* and JET contributors†

<sup>1</sup> UKAEA-CCFE, Culham Science Centre, Abingdon, Oxon, OX14 3DB, UK

<sup>2</sup> CEA, IRFM, F-13108 Saint-Paul-lez-Durance, France

<sup>3</sup> Max Planck Institute for Plasma Physics, Boltzmannstr. 2, 85748 Garching b. M., Germany

<sup>4</sup> Consorzio RFX, Corso Stati Uniti 4, 35127 Padova, Italy

<sup>5</sup> School of Physics, Beihang University, Beijing, 100191, China

<sup>6</sup> ITER Organization, Route de Vinon sur Verdon, CS 90 046, 13067 Saint Paul-lez-Durance, Cedex, France

<sup>7</sup> École Polytechnique Fédérale de Lausanne (EPFL), Swiss Plasma Center (SPC), CH-1015 Lausanne, Switzerland

<sup>8</sup> Massachusetts Institute of Technology, Cambridge, MA 02139, USA

Shattered pellet injection (SPI) is the current concept for the ITER disruption mitigation system (DMS) to prevent disruption-related damage from thermal loads, electromagnetic forces or runaway electron (RE) beams. Compared with impurity or mixed deuterium-impurity pellets that contain large quantity of impurities like neon, pure deuterium (D2) SPI is expected to strongly dilute the plasma without immediately triggering a thermal quench and could be instrumental for RE avoidance in ITER [1].

Detailed simulations of D2-SPI-induced disruptions, especially the (pre-)thermal quench phase in a JET discharge (#96874) with the JOREK code will be presented. In this discharge, a pure D2 pellet with a diameter of 12.5mm (barrel A) was shattered before entering the 3MA/2.9T H-mode plasma, exhibiting a much longer cooling time (~9ms between the arrival of the first shards at the plasma edge and the onset of thermal quench) than that with impurity pellets (typically 1~2ms). 3D non-linear MHD simulations show that the plasma is not fully cooled during the penetration and ablation of the D2 shards, allowing the current density ( $j$ ) to evolve on a much slower time scale than the penetration of the shards and no evident global contraction of  $j$  has been observed. Detailed comparison between simulations and experimental measurements will be presented to validate the model as well as clarify the underlying physics. In particular, the role of background impurities, pointed out as a concern in the predictions for ITER [1], will be examined in detail. Possible effects of plasma rotation on (pre-)thermal quench dynamics will also be discussed.

*This work has been carried out within the framework of the EUROfusion Consortium and has received funding from the Euratom research and training programme 2014-2018 and 2019-2020 under grant agreement No 633053 and from the RCUK [grant number EP/T012250/1]. The views and opinions expressed herein do not necessarily reflect those of the European Commission.*

## References:

[1] E. Nardon, D. Hu, M. Hoelzl, et al., *Nuclear Fusion* **60**, 126040 (2020)

---

\* See the author list of M. Hoelzl et al 2021 Nucl. Fusion 61 065001

† See the author list of ‘Overview of JET results for optimising ITER operation’ by J. Mailloux et al. to be published in Nuclear Fusion Special issue: Overview and Summary Papers from the 28th Fusion Energy Conference (Nice, France, 10-15 May 2021)