

Vector-like Spectra in F-theory 2

Muyang Liu

University of Pennsylvania

December 14, 2020

With M.Bies, M.Cvetič, R.Donagi, M.Ong – ongoing project

Set up background geometries

- One quadrillion threefold bases in F-theory compactifications classified by $\overline{K}_{B_3}^3$ value.

[Cvetič Halverson Lin [Liu](#) Tian '19]

Set up background geometries

- One quadrillion threefold bases in F-theory compactifications classified by $\overline{K}_{B_3}^3$ value.
[Cvetič Halverson Lin Liu Tian '19]
- Find line bundles to realize MSSM vector-like spectra:

Q_i	\bar{u}_i	\bar{d}_i	L_i	\bar{e}_i	H_u, H_d
(3, 0)	(3, 0)	(3, 0)	(3, 0)	(3, 0)	(1, 1)

Set up background geometries

- One quadrillion threefold bases in F-theory compactifications classified by $\overline{K}_{B_3}^3$ value.
[Cvetič Halverson Lin Liu Tian '19]
- Find line bundles to realize MSSM vector-like spectra:

Q_i	\bar{u}_i	\bar{d}_i	L_i	\bar{e}_i	H_u, H_d
(3, 0)	(3, 0)	(3, 0)	(3, 0)	(3, 0)	(1, 1)

⇒ This requires line bundles are subjected to conditions:

$$L^{\otimes n} = \overline{K}_{B_3}|_C^{\otimes m}, \quad \text{Quark-doublet curve: } L^{\otimes 3} = \overline{K}_{B_3}|_C^{\otimes 2}.$$

Set up background geometries

- One quadrillion threefold bases in F-theory compactifications classified by $\overline{K}_{B_3}^3$ value.

[Cvetič Halverson Lin Liu Tian '19]

- Find line bundles to realize MSSM vector-like spectra:

Q_i	\bar{u}_i	\bar{d}_i	L_i	\bar{e}_i	H_u, H_d
(3, 0)	(3, 0)	(3, 0)	(3, 0)	(3, 0)	(1, 1)

⇒ This requires line bundles are subjected to conditions:

$$L^{\otimes n} = \overline{K}_{B_3}|_C^{\otimes m}, \quad \text{Quark-doublet curve: } L^{\otimes 3} = \overline{K}_{B_3}|_C^{\otimes 2}.$$

- On a genus g curve, there are n^{2g} possible n -th roots.

$\overline{K}_{B_3}^3$	particles	genus	root type	degree of line bundle	root bundles counting
10	Q_i	6	5-th root	8	5^{12}
18	Q_i	10	3rd root	12	3^{20}
30	Q_i	16	5-th root	18	5^{32}

Set up background geometries

- One quadrillion threefold bases in F-theory compactifications classified by $\overline{K}_{B_3}^3$ value.

[Cvetič Halverson Lin Liu Tian '19]

- Find line bundles to realize MSSM vector-like spectra:

Q_i	\bar{u}_i	\bar{d}_i	L_i	\bar{e}_i	H_u, H_d
(3, 0)	(3, 0)	(3, 0)	(3, 0)	(3, 0)	(1, 1)

⇒ This requires line bundles are subjected to conditions:

$$L^{\otimes n} = \overline{K}_{B_3}|_C^{\otimes m}, \quad \text{Quark-doublet curve: } L^{\otimes 3} = \overline{K}_{B_3}|_C^{\otimes 2}.$$


- On a genus g curve, there are n^{2g} possible n -th roots.

$\overline{K}_{B_3}^3$	particles	genus	root type	degree of line bundle	root bundles counting
10	Q_i	6	5-th root	8	5^{12}
18	Q_i	10	3rd root	12	3^{20}
30	Q_i	16	5-th root	18	5^{32}

- On nodal curves: Root bundle constructions known. [Caporaso Casagrande Cornalba '04]


Proposal of MSSM construction

Good physics geometry X_{nodal}




Proposal of MSSM construction

Good physics geometry X_{nodal}




Artificial deform
→




Proposal of MSSM construction

Good physics geometry X_{nodal}




Artificial deform
→




By upper
semi-continuity
←
 h^0 remains 3

Proposal of MSSM construction

Good physics geometry X_{nodal}



Artificial deform
→



By upper
semi-continuity
←
 h^0 remains 3

- Anticipate complete MSSM vector-like spectra in good geometry X_{nodal}

- In the near future:
 - Look for physics geometries X_{nodal} .
 - Extend F-theory MSSM constructions to include vector-like spectra.

- In the near future:
 - Look for physics geometries X_{nodal} .
 - Extend F-theory MSSM constructions to include vector-like spectra.
- ⇒ Anticipate huge database from root bundle constructions as extension of <https://github.com/Learning-line-bundle-cohomology/Database>.

- In the near future:
 - Look for physics geometries X_{nodal} .
 - Extend F-theory MSSM constructions to include vector-like spectra.
 - ⇒ Anticipate huge database from root bundle constructions as extension of <https://github.com/Learning-line-bundle-cohomology/Database>.
- Explore database:
 - Statistics of MSSM vacua with exact vector-like spectra.
 - Learn construction strategies (reinforcement learning).

- In the near future:
 - Look for physics geometries X_{nodal} .
 - Extend F-theory MSSM constructions to include vector-like spectra.
 - ⇒ Anticipate huge database from root bundle constructions as extension of <https://github.com/Learning-line-bundle-cohomology/Database>.
- Explore database:
 - Statistics of MSSM vacua with exact vector-like spectra.
 - Learn construction strategies (reinforcement learning).
 - Long run: Yukawa interaction, particle masses, hierarchy structures ...
 - as extension of past work [Cvetič Lin Liu Zhang Zoccarato '19]

- In the near future:
 - Look for physics geometries X_{nodal} .
 - Extend F-theory MSSM constructions to include vector-like spectra.
 - ⇒ Anticipate huge database from root bundle constructions as extension of <https://github.com/Learning-line-bundle-cohomology/Database>.
- Explore database:
 - Statistics of MSSM vacua with exact vector-like spectra.
 - Learn construction strategies (reinforcement learning).
 - Long run: Yukawa interaction, particle masses, hierarchy structures ...
 - as extension of past work [Cvetič Lin Liu Zhang Zoccarato '19]
- Conceptual question:

intermediate Jacobian \leftrightarrow root/spin bundles.

Thank you for your attention!