



Performance of a MQXF Nb₃Sn quadrupole under different stress level

S. Izquierdo Bermudez, B. Bordini, N. Bourcey, S. Ferradas Troitino, J. Ferradas Troitino, L. Fiscarelli, J. Fleiter, M. Guinchard, F. Mangiarotti, J. C. Perez, E. Takala, E. Todesco, CERN, TE Department, MSC Group

G. Ambrosio, FNAL

P. Ferracin, LBNL



MT27 November 2021

The MQXF magnet

- Large aperture quadrupole for interaction region in the HL-LHC project
- Technology developed in LARP based on Nb₃Sn
 - RRP conductor, 0.85 mm diameter
- Six short model magnets built and tested (MQXFS)
- Eight 4.2-m-long MQXFA built and tested
- Two 7.15-m-long MQXFB built and tested
 - Installation in LHC tunnel starting in 2025
 - 16 MQXFA and 8 MQXFB around ATLAS and CMS
- Here we report about a relevant result of short model program, MQXFS6 obtained in 2019-2020



The MQXF magnet


- Magnet main parameters:
 - Large aperture (150 mm diameter)
 - Peak field of 11.3 T at nominal current (7 TeV)
 - Short sample at 14.5 T
 - Nb₃Sn conductor, Rutherford cable
 - Two layer coils, impregnated with CTD-101K
 - Bladder and key structure, Al shells
 - Scale-up of TQ and HQ LARP magnets

P. Ferracin, et al., *IEEE Trans. Appl. Supercond.* **26** (2016) 4000207


- Short model:

- All features of the long magnet, but 1.2 m long magnetic length
- The MQXFS6 coils were wound with PIT-192 strand, developed by Bruker
 - Two coils with PIT 192
 - Two coils with bundle barrier developed by Bruker and CERN

B. Bordini, et al., *IEEE Trans. Appl. Supercond.* **27** (2017) 6000706



MQXF cross-section (P. Ferracin, G Ambrosio)




PIT-192 and PIT-192 with bundle barrier

The MQXFS6 experiment


- The coil of the MQXFS magnet is preloaded via the mechanical structure to balance the effect of the electromagnetic forces at nominal current
 - This corresponds to having electromagnetic forces compensated by preload up to 80% of short sample current, and having 110 MPa azimuthal compression of the coil at 1.9 K
 - Careful control of preload is achieved, and the unloading a nominal current is measured via strain gauges
- In this experiment we verified the possibility of a lower preload
 - There is evidence in previous literature that a lower preload does not prevent to reach target currents (since SSC in the early 90's, [A. Devred, et al., AIP Conference Proceedings 249 \(1992\) 1309](#))
 - We tried a configuration with half of preload at 1.9 K (60 MPa), therefore giving electromagnetic forces compensated up to 60% of short sample
 - This is the lowest achievable preload with bladder and key structure, since
 - One has a positive contribution of cool-down to preload
 - One needs a minimal preload at room temperature to be able to handle the magnet

The mechanical data

- MQXFS6b: preload for nominal current (80% of short sample)
- MQXFS6c: preload for 60% of short sample
- Mechanical data during powering confirm the expected behaviour
 - MQXFS6b: unloading at $(I/I_{ss})^2=(0.8)^2\sim 0.64$
 - MQXFS6c: unloading at $(I/I_{ss})^2=(0.6)^2\sim 0.36$



Measured stresses during assembly, and FEM




Measured unloading during powering

(M. Guinchard, et al) E. Todesco

The quench performance


- MQXFS6b: (preloaded for 80% of short sample): 93% of short sample reached
- MQXFS6c: (preloaded for 60% of short sample): 89% of short sample reached
- MQXFS6d: (preloaded back to 80% of short sample): 95% of short sample reached, 13.4 T peak field



Powering of MQXFS6b-c-d (S. Ferradas Troitino, F. Mangiarotti, S. Izquierdo Bermudez et al.)

The quench performance

- As known in the literature since more than 30 years, currents larger than the corresponding preload value can be reached
 - In our case, preload as low as 60% of short sample allows reaching >85% of short sample
- In our case, higher preload reduces training in the region above 80% of short sample
- In our case, 80% preload rather than 60% allows reaching the highest performances (90%-95% of short sample)



Magnetic measurements

- A further cross-check of the lower preload: the variation of b_6 along the magnet ramp
 - Expected pole detachment provokes a change in first allowed multipole b_6
 - Measurements confirm that the **lower preload has larger pole detachment**

