


# Linear Colliders

## Lecture 4

Frank Tecker – CERN




- Damping rings
- NC/SC driven differences
- CLIC two beam scheme
- Drive Beam generation
- CLIC test facility CTF3



C.Pagani



- We have seen the different sub-systems in the previous lectures
- Now let's look at some differences in the real designs...


- **SC** allows long pulse, **NC** needs short pulse with smaller bunch charge



The different RF technologies used by ILC, NLC/JLC and CLIC require different packaging for the beam power

- Long pulse:  
 $950\mu\text{s} * c = 285 \text{ km}!!$
- Compress bunch train into 17 km (or less) “ring”  
kick individual bunches
- Min. circumference by ejection/injection kicker speed ( $\approx 20 \text{ ns}$ )
- “Dog bone” ring with  $\approx 400\text{m}$  of 1.67 T wigglers
- 3.2 km circular rings in the baseline ILC design
- Very demanding kicker rise + fall time  $< 6 \text{ ns}$





- Total length 421m (much smaller than ILC), beam pulse only 47m
- Racetrack shape with
  - 96 TME arc cells (4 half cells for dispersion suppression)
  - 26 Damping wiggler FODO cells in the long straight sections


## Normal Conducting

- High gradient  $\Rightarrow$  short linac 😊
- High rep. rate  $\Rightarrow$  ground motion suppression 😊
- Small structures  $\Rightarrow$  strong wakefields 😞
- Generation of high peak RF power 😞
- Small bunch distance 😞

## Superconducting



- long pulse  $\Rightarrow$  low peak power 😊
- large structure dimensions  $\Rightarrow$  low WF 😊
- very long pulse train  $\Rightarrow$  feedback within train 😊
- SC structures  $\Rightarrow$  high efficiency 😊
- Gradient limited  $<40$  MV/m  $\Rightarrow$  longer linac 😞  
(SC material limit  $\sim 55$  MV/m)
- low rep. rate  $\Rightarrow$  bad GM suppression  
( $\Sigma_y$  dilution) 😞
- Large number of e+ per pulse 😞
- very large DR 😞

- **Very high gradients** ( $>100$  MV/m) possible with NC accelerating structures at high RF frequencies ( $30$  GHz  $\rightarrow$   $12$  GHz)
- Extract required high RF power from an **intense** e- “**drive beam**”
- Generate **efficiently** long pulse and compress it (in power + frequency)




- High charge **Drive Beam** (low energy)
- Low charge **Main Beam** (high collision energy)
- => Simple tunnel, no active elements
- => Modular, easy energy upgrade in stages

**CLIC TUNNEL CROSS-SECTION**








*Counter propagation from central complex*

Instead of using a single drive beam pulse for the whole main linac, several ( $N_S = 25$ ) short drive beam pulses are used

Each one feed a  $\sim 880$  m long sector of two-beam acceleration (TBA)




Counter flow distribution allows to power different sectors of the main linac with different time bins of a single long electron drive beam pulse



The distance between the pulses is  $2 L_s = 2 L_{\text{main}}/N_S$  ( $L_{\text{main}}$  = single side linac length)

The initial drive beam pulse length  $t_{\text{DB}}$  is given by twice the time of flight through one single linac


$$\text{so } t_{\text{DB}} = 2 L_{\text{main}} / c, \quad 148 \mu\text{s for the 3 TeV CLIC}$$




## Drive beam time structure - initial



## Drive beam time structure - final



# Lemmings Drive Beam





Alexandra  
Andersson

- **efficient** power transfer from RF to the beam needed


“Standard” situation:

- **small** beam loading
- power at structure exit lost in load



“Efficient” situation:

- high beam current
- **high** beam loading
- no power flows into load
- $V_{ACC} \approx 1/2 V_{unloaded}$




- Disadvantage: any current variation changes energy gain

$$\frac{dV / V}{dI_{beam} / I_{beam}} = - \frac{I_{beam}}{I_{opt}}$$


at full loading, 1% current variation = 1% voltage variation

at 20% loading, 1% current variation = 0.2% voltage variation


- Requires **high current stability**
- Stable beam successfully demonstrated in CTF3
- > 95% efficiency**



- basic principle of **drive beam** generation
- transform very long pulses into short pulses with higher power and higher frequency
- use **RF deflectors** to **interleave** bunches
  - => double power
  - => double frequency





- double repetition frequency and current
- parts of bunch train delayed in loop
- RF deflector combines the bunches ( $f_{defl} = \text{bunch rep. frequency}$ )
- Path length corresponds to beam pulse length







● combination factors up to 5 reachable in a ring

$$C_{ring} = (n + 1/4) L$$




$C_{ring}$  has to correspond to the distance of pulses from the previous combination stage!



## Combination factor 5


### CTF3 - PRELIMINARY PHASE 2001/2002

Successful low-charge demonstration of electron pulse combination and bunch frequency multiplication by up to factor 5





streak camera measurement

RF deflectors




Beam time structure in linac




Beam structure after combination

Streak camera image of beam time structure evolution



RF injection in combiner ring


Combination factor 4





Streak camera images of the beam, showing the bunch combination process

A first ring combination test was performed in 2002, *at low current and short pulse*, in the CERN Electron-Positron Accumulator (EPA), properly modified

- demonstrate remaining **CLIC feasibility** issues, in particular:
  - **Drive Beam generation** (fully loaded acceleration, bunch frequency multiplication)
  - **CLIC accelerating structures**
  - **CLIC power production structures (PETS)**





- combined operation of Delay Loop and Combiner Ring (factor 8 combination)
- ~26 A combination reached, nominal 140 ns pulse length
- => **Full drive beam generation, main goal of 2009, achieved**





- must **extract** efficiently **>100 MW power** from high current drive beam
- passive microwave device in which bunches of the drive beam interact with the impedance of the periodically loaded waveguide and generate RF power
- periodically corrugated structure with low impedance (big  $a/\lambda$ )
- ON/OFF mechanism



The power produced by the bunched ( $\omega_0$ ) beam in a constant impedance structure:

$$P = I^2 L^2 F_b^2 W_0 \frac{\overset{\text{Design input parameters}}{\uparrow} \overset{\text{PETS design}}{\hat{R}/Q}}{4v_g}$$


$P$  - RF power, determined by the accelerating structure needs and the module layout.

$I$  - Drive beam current

$L$  - Active length of the PETS

$F_b$  - single bunch form factor ( $\approx 1$ )

- RF breakdowns can occur => no acceleration and deflection




- Goal:  $3 \cdot 10^{-7}/m$  breakdowns at 100 MV/m loaded gradient at 230 ns pulse length

- latest prototypes (T24 and TD24) tested (SLAC and KEK)

- => TD24 reach up to 108 MV/m at nominal CLIC breakdown rate (without damping material)

- Undamped T24 reaches 120MV/m




time: 0 0 . 0 ns

Accelerating structure

- The induced fields travel along the PETS structure and build up resonantly

PETS structure



Low group velocity requires simulations with 100k time steps



T3P models realistic, complex accelerator structures with unprecedented accuracy



Arno Candel, SLAC







- Drive beam has high current and high energy spread
- Stable transport in simulations verified experimentally with 13 PETS
- 24 A beam decelerated by ~51%, >1.3 GW power produced!
- Good agreement of power production, beam current and deceleration



Maximum probe beam acceleration measured: **31 MeV**

=> Corresponding to a gradient of **145 MV/m**






## Vol 1: The CLIC accelerator and site facilities (H.Schmickler)

- CLIC concept with exploration over multi-TeV energy range up to 3 TeV
- Feasibility study of CLIC parameters optimized at 3 TeV (most demanding)
- Consider also 500 GeV, and intermediate energy range
- Complete, presented in SPC in March 2011, in print: <https://edms.cern.ch/document/1234244/>


In addition a shorter overview document as input to the European Strategy update, available at: <http://arxiv.org/pdf/1208.1402v1>



## Vol 2: Physics and detectors at CLIC (L.Linssen)


- Physics at a multi-TeV CLIC machine can be measured with high precision, despite challenging background conditions
- External review procedure in October 2011
- Completed and printed, presented in SPC in December 2011 <http://arxiv.org/pdf/1202.5940v1>

**2016:**  
CLIC Baseline update  
After Higgs discovery  
<https://cds.cern.ch/record/2210892/>



## Vol 3: "CLIC study summary" (S.Stapnes)

- Summary and available for the European Strategy process, including possible implementation stages for a CLIC machine as well as costing and cost-drives
- Proposing objectives and work plan of post CDR phase (2012-16)
- Completed and printed, submitted for the European Strategy Open Meeting in September <http://arxiv.org/pdf/1209.2543v1>





## CLIC input to the European Strategy for Particle Physics Update 2018-2020

### *Formal European Strategy submissions*

- **The Compact Linear e+e- Collider (CLIC): Accelerator and Detector** ([arXiv:1812.07987](https://arxiv.org/abs/1812.07987))
- **The Compact Linear e+e- Collider (CLIC): Physics Potential** ([arXiv:1812.07986](https://arxiv.org/abs/1812.07986))

### *Yellow Reports*

- **CLIC 2018 Summary Report** ([CERN-2018-005-M](https://cds.cern.ch/record/2311111), [arXiv:1812.06018](https://arxiv.org/abs/1812.06018))
- **CLIC Project Implementation Plan** ([CERN-2018-010-M](https://cds.cern.ch/record/2311111))
- **The CLIC potential for new physics** ([CERN-2018-009-M](https://cds.cern.ch/record/2311111))
- **Detector technologies for CLIC** [In collaboration review]

### *Journal publications*

- **Top-quark physics at the CLIC electron-positron linear collider** [In journal review] ([arXiv:1807.02441](https://arxiv.org/abs/1807.02441))
- **Higgs physics at the CLIC electron-positron linear collider** ([Journal](#), [arXiv:1608.07538](https://arxiv.org/abs/1608.07538))
  - Projections based on the analyses from this paper scaled to the latest assumptions on integrated luminosities can be found here: [CDS](#), [arXiv](#).

### *CLICdp notes*

- **Updated CLIC luminosity staging baseline and Higgs coupling prospects** ([CERN Document Server](#), [arXiv:1812.01644](https://arxiv.org/abs/1812.01644))
- **CLICdet: The post-CDR CLIC detector model** ([CERN Document Server](#))
- **A detector for CLIC: main parameters and performance** ([CERN Document Server](#), [arXiv:1812.07337](https://arxiv.org/abs/1812.07337))

**Link:** <http://clic.cern/european-strategy>

### 2013 - 2019 Development Phase

Development of a Project Plan for a staged CLIC implementation in line with LHC results; technical developments with industry, performance studies for accelerator parts and systems, detector technology demonstrators

### 2020 - 2025 Preparation Phase

Finalisation of implementation parameters, preparation for industrial procurement, Drive Beam Facility and other system verifications, Technical Proposal of the experiment, site authorisation

### 2026 - 2034 Construction Phase

Construction of the first CLIC accelerator stage compatible with implementation of further stages; construction of the experiment; hardware commissioning

### 2019 - 2020 Decisions

Update of the European Strategy for Particle Physics; decision towards a next CERN project at the energy frontier (e.g. CLIC, FCC)

### 2025 Construction Start

Ready for construction; start of excavations

### 2035 First Beams

Getting ready for data taking by the time the LHC programme reaches completion



- Linear e<sup>+</sup>/e<sup>-</sup> Collider the only realistic approach to highest energy
- **Many challenges!!!**
- Efficient acceleration
  - RF system
  - High gradient
- Extremely small beam sizes
  - Damping ring performance is crucial
  - Emittance preservation
  - Alignment and stabilisation
- **Much interesting work left to do!!!**
- Much more detailed lectures at recent ILC schools  
<http://agenda.linearcollider.org/event/6906> or  
<http://agenda.linearcollider.org/event/7333>
- Some nice animations for CLIC on <http://clic.cern>