



Contribution ID: 41

Type: **not specified**

ATLAS ITk Pixel Detector Overview

Thursday 18 March 2021 09:23 (18 minutes)

For the HL-LHC upgrade the current ATLAS Inner Detector is replaced by an all-silicon system. The Pixel Detector will consist of 5 barrel layers and a number of rings, resulting in about 14 m² of instrumented area. Due to the huge non-ionizing fluence ($1e16$ neq/cm²) and ionizing dose (5 MGy), the two innermost layers, instrumented with 3D pixel sensors (L0) and 100 μ m thin planar sensors (L1) will be replaced after about 5 years of operation. All hybrid detector modules will be read out by novel ASICs, implemented in 65nm CMOS technology, with a bandwidth of up to 5 Gb/s. Data will be transmitted optically to the off-detector readout system. To save material in the servicing cables, serial powering is employed for low voltage. Large scale prototyping programs are being carried out by all sub-systems. The talk will give an overview of the layout and current status of the development of the ITk Pixel Detector.

Time Zone

Europe/Africa/Middle East

Primary authors: MUNOZ SANCHEZ, Francisca (University of Manchester (GB)); WEINGARTEN, Jens (Technische Universitaet Dortmund (DE))

Presenter: MENG, Lingxin (CERN)

Session Classification: PD5: Tracking Detectors

Track Classification: Physics and Detectors Tracks: PD5: Tracking Detectors