

SURVEY PSB 2013

Measurement and alignment results

SURVEY PSB 2013

- What has been done
- Requests and Constraints
- Results and Conclusion

SURVEY PSB 2013


- What has been done
 - Measurements in vertical, transversal tilt, radial, and longitudinal direction
 - All dipoles, quads, BPM's
 - Height measurement with optical level
 - Tilt measurement with special tool (quads) and electronical spirit level for bends and BPM's
 - Radial measurement with stretched nylon wire and theodolite
 - Distances with AT401 (high precision total station)

SURVEY PSB 2013


- **Measurement results**
 - Vertical and tilt offsets
 - Radial and longitudinal offsets

SURVEY PSB 2013

PSB, levelling 2013




SURVEY PSB 2013



SURVEY PSB 2013


- **Requests and constraints**
 - SU delivered these results to OP
 - A proposal for the partial vertical and radial alignment was made by OP, including tilt alignment of the quads and 3 dipoles and suppression of the bumps.
 - Vertical: around a smooth curve proposed by OP
 - Radial: quads and BPM's to 0, and bends remaining at their actual position, besides 3 where the tilt should be corrected.
 - Discussions with RP and VAC (ALARA, chamber constraints)

SURVEY PSB 2013




SURVEY PSB 2013

Final radial positions, zero fit



SURVEY PSB 2013

PSB - radial positions (quads, bends, BPM's) after alignment



SURVEY PSB 2013

- **Conclusions**

- SU measured and aligned the quads and BPM's of the PSB
- In the vertical plane, the results are within $\pm 0.5\text{mm}$ around the proposed smooth curve.
- In radial, besides some exceptions due to access constraints to the moving devices / screws, the solution «3B» (quad zero fit) could be applied.
- We are now looking forward to «see» the beam pass into and turn in this «new» machine.